

San Bernardino County Behavioral Health Comprehensive Treatment Center Air Quality, Greenhouse Gas, and Energy Impact Study City of Victorville, CA

Prepared for:

Ms. Kayti Christianson
Terracon
145 W Walnut St.
Carson, CA

Prepared by:

MD Acoustics, LLC
Tyler Klassen, EIT
1197 Los Angeles Ave, Ste C-256
Simi Valley, CA 93065

Date: 6/2/2025

MDACOUSTICS
Sound Solutions for Planning and Design

Noise Study Reports | Vibration Studies | Air Quality | Greenhouse Gas | Health Risk Assessments

P) AZ - 602.774.1950

P) CA - 805.426.4477

www.mdacoustics.com
info@mdacoustics.com

TABLE OF CONTENTS

1.0	Introduction	1
1.1	Purpose of Analysis and Study Objectives	1
1.2	Project Summary	1
1.2.1	Site Location	1
1.2.2	Project Description	1
1.2.3	Sensitive Receptors	1
1.3	Executive Summary of Findings and Mitigation Measures	2
2.0	Regulatory Framework and Background	5
2.1	Air Quality Regulatory Setting	5
2.1.1	National and State	5
2.1.2	Mojave Desert Air Quality Management District	7
2.1.3	City of Victorville	10
2.2	Greenhouse Gas Regulatory Setting	11
2.2.1	International	11
2.2.2	National	12
2.2.3	California	15
2.2.4	Mojave Desert Air Quality Management District	22
2.2.5	City of Victorville	23
3.0	Setting	24
3.1	Existing Physical Setting	24
3.1.1	Local Climate and Meteorology	24
3.1.2	Local Air Quality	25
3.1.3	Attainment Status	27
3.2	Greenhouse Gases	28
4.0	Modeling Parameters and Assumptions	30
4.1	Construction	30
4.2	Operations	30
5.0	Thresholds of Significance	32
5.1	Air Quality Thresholds of Significance	32
5.1.1	CEQA Guidelines for Air Quality	32
5.1.2	Regional Significance Thresholds	32
5.2	Greenhouse Gas Thresholds of Significance	33
5.2.1	CEQA Guidelines for Greenhouse Gas	33
6.0	Air Quality Emissions Impact	34
6.1	Construction Air Quality Emissions Impact	34
6.1.1	Regional Construction Emissions	34
6.1.3	Odors	34

6.1.4	Construction-Related Toxic Air Contaminant Impact	35
6.2	Operational Air Quality Emissions Impact	35
6.2.1	Regional Operational Emissions	35
6.2.2	Operations-Related Toxic Air Contaminant Impacts	36
6.2.3	Operations-Related Odor Impacts	36
6.3	Cumulative Regional Air Quality Impacts	37
6.4	Air Quality Compliance	37
7.0	Greenhouse Gas Impact Analysis.....	39
7.1	Construction Greenhouse Gas Emissions Impact	39
7.2	Operational Greenhouse Gas Emissions Impact	39
7.3	Greenhouse Gas Plan Consistency	40
7.4	Cumulative Greenhouse Gas Impacts	41
8.0	Energy Analysis.....	42
8.1	Construction Energy Demand	42
8.1.1	Construction Equipment Electricity Usage Estimates	42
8.1.2	Construction Equipment Fuel Estimates	43
8.1.3	Construction Worker Fuel Estimates	43
8.1.4	Construction Vendor/Hauling Fuel Estimates	44
8.1.5	Construction Energy Efficiency/Conservation Measures	45
8.2	Operational Energy Demand	45
8.2.1	Transportation Fuel Consumption	45
8.2.2	Facility Energy Demands (Electricity and Natural Gas)	46
8.3	Renewable Energy and Energy Efficiency Plan Consistency	47
9.0	References.....	48

LIST OF APPENDICES

Appendix A:
CalEEMod Emissions Output

Appendix B:
EMFAC2021 Output

LIST OF EXHIBITS

Exhibit A **3**
Location Map 3

Exhibit B **4**
Site Plan 4

LIST OF TABLES

Table 1: Land Use Summary..... 1

Table 2: Ambient Air Quality Standards 6

Table 3: MDAQMD Air Quality Significance Thresholds 22

Table 4: Meteorological Summary..... 25

Table 5: Local Area Air Quality Levels 26

Table 6: Attainment Status of MDAQMD – Portion of Mojave Desert Air Basin 28

Table 7: Description of Greenhouse Gases..... 29

Table 8: Regional Significance - Construction Emissions (pounds/day) 34

Table 9: Regional Significance - Operational Emissions (tons/year) 36

Table 10: Construction Greenhouse Gas Emissions 39

Table 11: Opening Year Project-Related Greenhouse Gas Emissions 40

Table 12: Project Construction Power Cost and Electricity Usage 42

Table 13: Construction Equipment Fuel Consumption Estimates 43

Table 14: Construction Worker Fuel Consumption Estimates 44

Table 15: Construction Vendor Fuel Consumption Estimates (MHD Trucks)..... 44

Table 16: Construction Hauling Fuel Consumption Estimates (HHD Trucks) 45

Table 17: Estimated Vehicle Operations Fuel Consumption 46

Table 18: Project Unmitigated Annual Operational Energy Demand Summary 47

GLOSSARY OF TERMS

AQMP	Air Quality Management Plan
CAAQS	California Ambient Air Quality Standards
CARB	California Air Resources Board
CEQA	California Environmental Quality Act
CFCs	Chlorofluorocarbons
CH ₄	Methane
CNG	Compressed natural gas
CO	Carbon monoxide
CO ₂	Carbon dioxide
CO ₂ e	Carbon dioxide equivalent
DPM	Diesel particulate matter
GHG	Greenhouse gas
HFCs	Hydrofluorocarbons
MDAB	Mojave Desert Air Basin
MDAQMD	Mojave Desert Air Quality Management District
MTCO ₂ e	Metric tons of carbon dioxide equivalent
MMTCO ₂ e	Million metric tons of carbon dioxide equivalent
NAAQS	National Ambient Air Quality Standards
NO _x	Nitrogen Oxides
NO ₂	Nitrogen dioxide
N ₂ O	Nitrous oxide
O ₃	Ozone
PFCs	Perfluorocarbons
PM	Particle matter
PM ₁₀	Particles that are less than 10 micrometers in diameter
PM _{2.5}	Particles that are less than 2.5 micrometers in diameter
PMI	Point of maximum impact
PPM	Parts per million
PPB	Parts per billion
RTIP	Regional Transportation Improvement Plan
RTP	Regional Transportation Plan
SF ₆	Sulfur hexafluoride
SIP	State Implementation Plan
SO _x	Sulfur Oxides
SRA	Source/Receptor Area
TAC	Toxic air contaminants
VOC	Volatile organic compounds
WRCC	Western Regional Climate Center

1.0 Introduction

1.1 Purpose of Analysis and Study Objectives

This air quality and greenhouse gas (GHG) analysis was prepared to evaluate whether the estimated criteria pollutants and GHG emissions generated from the project would cause a significant impact to the air resources in the project area. This assessment was conducted within the context of the California Environmental Quality Act (CEQA, California Public Resources Code Sections 21000, et seq.). The assessment is consistent with the methodology and emission factors endorsed by Mojave Desert Air Quality Management District (MDAQMD), California Air Resource Board (CARB), and the United States Environmental Protection Agency (US EPA).

1.2 Project Summary

1.2.1 Site Location

The project site is located at 13333 Palmdale Road in the City of Victorville, California, as shown in Exhibit A. The site is zoned as Low Density Residential according to the City of Victorville General Plan Zoning Map. Land uses surrounding the site include vacant land to the north and west, a middle school to the south, and a high school across Cobalt Road to the east.

1.2.2 Project Description

The proposed Project is the improvement and expansion of the St. John of God Health Care Services center into the San Bernardino County Behavioral Health Comprehensive Treatment Campus, including 138 new patient beds. Exhibit B demonstrates the site plan for the project.

Construction activities within the Project area will consist of site preparation, on-site grading, building, paving, and architectural coating. Table 1 summarizes the land use description for the Project Site.

Table 1: Land Use Summary

Land Use	Unit Amount	Size Metric
Congregate Care (Assisted Living)	138	Dwelling Units
Parking Lot	261	Spaces

1.2.3 Sensitive Receptors

Sensitive receptors are considered land uses or other types of population groups that are more sensitive to air pollution than others due to their exposure. Sensitive population groups include children, the elderly, the acutely and chronically ill, and those with cardio-respiratory diseases. For CEQA purposes, a sensitive receptor would be a location where a sensitive individual could remain for 24-hours or longer, such as residences, hospitals, and schools (etc.).

The closest existing sensitive receptors (to the site area) are the middle school located 100 feet to the south and high school located 300 feet to the east.

1.3 Executive Summary of Findings and Mitigation Measures

The following is a summary of the analysis results:

Construction-Source Emissions

Project construction-source emissions would not exceed applicable regional thresholds of significance established by the MDAQMD.

As discussed herein, the project will comply with all applicable MDAQMD construction-source emission reduction rules and guidelines. Project construction source emissions would not cause or substantively contribute to violation of the California Ambient Air Quality Standards (CAAQS) or National Ambient Air Quality Standards (NAAQS).

Established requirements addressing construction equipment operations, and construction material use, storage, and disposal requirements act to minimize odor impacts that may result from construction activities. Moreover, construction-source odor emissions would be temporary, short-term, and intermittent in nature and would not result in persistent impacts that would affect substantial numbers of people. Potential construction-source odor impacts are therefore considered less-than-significant.

Operational-Source Emissions

The project's emissions meet MDAQMD regional thresholds and will not result in a significant cumulative impact. The project does not propose any such uses or activities that would result in potentially significant operational-source odor impacts. Potential operational-source odor impacts are therefore considered less-than-significant.

Project-related GHG emissions meet the MDAQMD and City of Victorville thresholds and are also considered to be less than significant. The project also complies with the goals of the CARB Scoping Plan, AB-32, and SB-32.

Mitigation Measures

A. Construction Measures

The project applicant shall ensure that all applicable MDAQMD Rules and Regulations are complied with during construction.

No construction measures are required.

B. Operational Measures to Reduce GHG Emissions

No operational measures are required.

Exhibit A Location Map



2.0 Regulatory Framework and Background

2.1 Air Quality Regulatory Setting

Air pollutants are regulated at the national, state, and air basin level; each agency has a different level of regulatory responsibility. The United States Environmental Protection Agency (EPA) regulates at the national level. The California Air Resources Board (ARB) regulates at the state level. The Mojave Desert Air Quality Management District (MDAQMD) regulates at the air basin level.

2.1.1 National and State

The EPA is responsible for global, international, and interstate air pollution issues and policies. The EPA sets national vehicle and stationary source emission standards, oversees approval of all State Implementation Plans, provides research and guidance for air pollution programs, and sets National Air Quality Standards, also known as federal standards. There are six common air pollutants, called criteria pollutants, which were identified from the provisions of the Clean Air Act of 1970.

- Ozone
- Nitrogen Dioxide
- Lead
- Particulate Matter (PM10 and PM2.5)
- Carbon Monoxide
- Particulate Matter
- Sulfur Dioxide

The federal standards were set to protect public health, including that of sensitive individuals; thus, the standards continue to change as more medical research is available regarding the health effects of the criteria pollutants. Primary federal standards are the levels of air quality necessary, with an adequate margin of safety, to protect the public health.

A State Implementation Plan is a document prepared by each state describing existing air quality conditions and measures that will be followed to attain and maintain federal standards. The State Implementation Plan for the State of California is administered by the ARB, which has overall responsibility for statewide air quality maintenance and air pollution prevention. California's State Implementation Plan incorporates individual federal attainment plans for regional air districts—air district prepares their federal attainment plan, which sent to ARB to be approved and incorporated into the California State Implementation Plan. Federal attainment plans include the technical foundation for understanding air quality (e.g., emission inventories and air quality monitoring), control measures and strategies, and enforcement mechanisms. See <http://www.arb.ca.gov/research/aaqs/aaqs.htm> for additional information on criteria pollutants and air quality standards.

The federal and state ambient air quality standards are summarized in Table 2 and can also be found at <http://www.arb.ca.gov/research/aaqs/aaqs2.pdf>.

Table 2: Ambient Air Quality Standards

Pollutant	Averaging Time	California Standards ¹		National Standards ²		
		Concentrations ³	Method ⁴	Primary ^{3,5}	Secondary ^{3,6}	Method ⁷
Ozone (O ₃)	1-Hour	0.09 ppm	Ultraviolet Photometry	--	Same as Primary Standard	Ultraviolet Photometry
	8-Hour	0.070 ppm		0.070 ppm (147 µg/m ³)		
Respirable Particulate Matter (PM ₁₀) ⁸	24-Hour	50 µg/m ³	Gravimetric or Beta Attenuation	150 µ/m ³	Same as Primary Standard	Inertial Separation and Gravimetric Analysis
	Annual Arithmetic Mean	20 µg/m ³		--		
Fine Particulate Matter (PM _{2.5}) ⁸	24-Hour	--	--	35 µg/m ³	Same as Primary Standard	Inertial Separation and Gravimetric Analysis
	Annual Arithmetic Mean	12 µg/m ³	Gravimetric or Beta Attenuation	12 µg/m ³		
Carbon Monoxide (CO)	1-Hour	20 ppm (23 µg/m ³)	Non-Dispersive Infrared Photometry (NDIR)	35 ppm (40 µg/m ³)	--	Non-Dispersive Infrared Photometry (NDIR)
	8-Hour	9.0 ppm (10 µg/m ³)		9 ppm (10 µg/m ³)	--	
	8-Hour (Lake Tahoe)	6 ppm (7 µg/m ³)		--	--	
Nitrogen Dioxide (NO ₂) ⁹	1-Hour	0.18 ppm (339 µg/m ³)	Gas Phase Chemiluminescence	100 ppb (188 µg/m ³)	--	Gas Phase Chemiluminescence
	Annual Arithmetic Mean	0.030 ppm (357 µg/m ³)		0.053 ppm (100 µg/m ³)	Same as Primary Standard	
Sulfur Dioxide (SO ₂) ¹⁰	1-Hour	0.25 ppm (655 µg/m ³)	Ultraviolet Fluorescence	75 ppb (196 µg/m ³)	--	Ultraviolet Fluorescence; Spectrophotometry (Pararosaniline Method)
	3-Hour	--		--	0.5 ppm (1300 µg/m ³)	
	24-Hour	0.04 ppm (105 µg/m ³)		0.14 ppm (for certain areas) ¹⁰	--	
	Annual Arithmetic Mean	--		0.130ppm (for certain areas) ¹⁰	--	
Lead ^{11,12}	30 Day Average	1.5 µg/m ³	Atomic Absorption	--	Same as Primary Standard	High Volume Sampler and Atomic Absorption
	Calendar Qtr	--		1.5 µg/m ³ (for certain areas) ¹²		
	Rolling 3-Month Average	--		0.15 µg/m ³		
Visibility Reducing Particles ¹³	8-Hour	See footnote 13	Beta Attenuation and Transmittance through Filter Tape	No National Standards		
Sulfates	24-Hour	25 µg/m ³	Ion Chromatography			
Hydrogen Sulfide	1-Hour	0.03 ppm (42 µg/m ³)	Ultraviolet Fluorescence			
Vinyl Chloride ¹¹	24-Hour	0.01 ppm (26 µg/m ³)	Gas Chromatography			

Notes:

- California standards for ozone, carbon monoxide (except 8-hour Lake Tahoe), sulfur dioxide (1 and 24 hour), nitrogen dioxide, and particulate matter (PM₁₀, PM_{2.5}, and visibility reducing particles), are values that are not to be exceeded. All others are not to be equaled or exceeded. California ambient air quality standards are listed in the Table of Standards in Section 70200 of Title 17 of the California Code of Regulations.
- National standards (other than ozone, particulate matter, and those based on annual arithmetic mean) are not to be exceeded more than once a year. The ozone standard is attained when the fourth highest 8-hour concentration measured at each site in a year, averaged over three years, is equal to or less than the standard. For PM₁₀, the 24 hour standard is attained when the expected number of days per calendar year with a 24-hour average concentration above 150 µg/m³ is equal to or less than one. For PM_{2.5}, the 24 hour standard is attained when 98 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. Contact the U.S. EPA for further clarification and current national policies.
- Concentration expressed first in units in which it was promulgated. Equivalent units given in parentheses are based upon a reference temperature of 25°C and a reference pressure of 760 torr. Most measurements of air quality are to be corrected to a reference temperature of 25°C and a reference pressure of 760 torr; ppm in this table refers to ppm by volume, or micromoles of pollutant per mole of gas.
- Any equivalent measurement method which can be shown to the satisfaction of the ARB to give equivalent results at or near the level of the air quality standard may be used.
- National Primary Standards: The levels of air quality necessary, with an adequate margin of safety to protect the public health.
- National Secondary Standards: The levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant.
- Reference method as described by the U.S. EPA. An "equivalent method" of measurement may be used but must have a "consistent relationship to the reference method" and must be approved by the U.S. EPA.

8. On December 14, 2012, the national annual PM_{2.5} primary standard was lowered from 15 µg/m³ to 12.0 µg/m³. The existing national 24-hour PM_{2.5} standards (primary and secondary) were retained at 35 µg/m³, as was the annual secondary standard of 15 µg/m³. The existing 24-hour PM₁₀ standards (primary and secondary) of 150 µg/m³ also were retained. The form of the annual primary and secondary standards is the annual mean, averaged over 3 years.
9. To attain the 1-hour national standard, the 3-year average of the annual 98th percentile of the 1-hour daily maximum concentrations at each site must not exceed 100 ppb. Note that the national 1-hour standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the national 1-hour standard to the California standards the units can be converted from ppb to ppm. In this case, the national standard of 100 ppb is identical to 0.100 ppm.
10. On June 2, 2010, a new 1-hour SO₂ standard was established and the existing 24-hour and annual primary standards were revoked. To attain the 1-hour national standard, the 3-year average of the annual 99th percentile of the 1-hour daily maximum concentrations at each site must not exceed 75 ppb. The 1971 SO₂ national standards (24-hour and annual) remain in effect until one year after an area is designated for the 2010 standard, except that in areas designated nonattainment for the 1971 standards, the 1971 standards remain in effect until implementation plans to attain or maintain the 2010 standards are approved.

Note that the 1-hour national standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the 1-hour national standard to the California standard the units can be converted to ppm. In this case, the national standard of 75 ppb is identical to 0.075 ppm.

11. The ARB has identified lead and vinyl chloride as 'toxic air contaminants' with no threshold level of exposure for adverse health effects determined. These actions allow for the implementation of control measures at levels below the ambient concentrations specified for these pollutants.
12. The national standard for lead was revised on October 15, 2008 to a rolling 3-month average. The 1978 lead standard (1.5 µg/m³ as a quarterly average) remains in effect until one year after an area is designated for the 2008 standard, except that in areas designated nonattainment for the 1978 standard, the 1978 standard remains in effect until implementation plans to attain or maintain the 2008 standard are approved.
13. In 1989, the ARB converted both the general statewide 10-mile visibility standard and the Lake Tahoe 30-mile visibility standard to instrumental equivalents, which are "extinction of 0.23 per kilometer" and "extinction of 0.07 per kilometer" for the statewide and Lake Tahoe Air Basin standards, respectively.

Several pollutants listed in Table 2 are not addressed in this analysis. Analysis of lead is not included in this report because the project is not anticipated to emit lead. Visibility-reducing particles are not explicitly addressed in this analysis because particulate matter is addressed. The project is not expected to generate or be exposed to vinyl chloride because proposed project uses do not utilize the chemical processes that create this pollutant and there are no such uses in the project vicinity. The proposed project is not expected to cause exposure to hydrogen sulfide because it would not generate hydrogen sulfide in any substantial quantity.

2.1.2 Mojave Desert Air Quality Management District

The 1976 Lewis Air Quality Management Act established the MDAQMD and other air districts throughout the State. The federal CAA Amendments of 1977 required that each state adopt an implementation plan outlining pollution control measures to attain the federal standards in nonattainment areas of the state.

The ARB is responsible for incorporating air quality management plans for local air basins into a State Implementation Plan (SIP) for EPA approval. Significant authority for air quality control within them has been given to local air districts that regulate stationary source emissions and develop local nonattainment plans.

California is divided geographically into air basins for the purpose of managing the air resources of the State on a regional basis. An air basin generally has similar meteorological and geographic conditions throughout. The State is currently divided into 15 air basins. The proposed project site is located within

the Mojave Desert Air Basin (MDAB). The MDAQMD includes the desert portion of the San Bernardino County. The MDAQMD is responsible for controlling emissions primarily from stationary sources within the MDAQMD and also maintains air quality monitoring stations to document historical and current levels of air quality within the District. The MDAQMD is also responsible for developing, updating, and implementing the Ozone Attainment Plan (MDAQMD 2004) which establishes a plan to implement, maintain, and enforce a program of emission control measures to attain and maintain the federal ozone air quality standards. Attainment plans prepared by the various air pollution control districts throughout the state are used to develop the SIP for the State of California. The proposed project is located within the MDAQMD and, thus, is subject to the rules and regulations of the MDAQMD.

The MDAQMD and SCAG are responsible for formulating and implementing the air quality attainment plan (AQAP) for the Basin. Regional AQAPs were adopted in 1991, 1994, and 1997. The following SIP and AQAP are the currently approved plans for the Basin region:

- 1997 SIP for O₃, PM₁₀, and NO₂
- 1995 Mojave Desert Planning Area Federal PM₁₀ Attainment Plan; no formal action by the EPA

The MDAQMD completed the MDAQMD 2004 Ozone Attainment Plan (State and federal) in April 2004, which has been approved by the EPA.

The MDAQMD is downwind of the Los Angeles basin and the San Joaquin Valley. Prevailing winds transport ozone and ozone precursors from both regions into and through the MDAB during the summer ozone season. These transport couplings have been officially recognized by the CARB. Local MDAQMD emissions contribute to exceedances of both the NAAQS and CAAQS for ozone, but photochemical ozone modeling conducted by the MDAQMD and CARB indicates that the MDAB would be in attainment of both standards without the influence of this transported air pollution from upwind regions. Therefore, emissions reductions in the upwind area are critical to the attainment demonstration.

The following includes, but is not limited to, the MDAQMD rules that are applicable to the proposed project:

Rule 201 (Permit to Construct) requires written authorization to build, erect, install, alter, or replace any equipment, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants. With respect to the proposed project, this rule would apply to any stationary equipment that is not otherwise exempt from this rule as an insignificant source of air pollutants (see Rule 219).

Rule 203 (Permit to Operate) requires written authorization to operate any equipment, the use of which may cause the issuance of air pollutants, or the use of which may reduce or control the issuance of air contaminants. With respect to the proposed project, this rule would apply to any stationary equipment that is not otherwise exempt from this rule as an insignificant source of air pollutants (see Rule 219).

Rule 219 (Equipment Not Requiring A Written Permit Pursuant to Regulation II) specifies stationary sources that the MDAQMD considers to be insignificant sources of air pollutants that are exempt from

Rules 201 and 202. With respect to the proposed project, the following sources would be exempt from permit requirements:

- Comfort air conditioning or ventilating systems which are not designed or used to remove air contaminants generated by, or released from, specific equipment units;
- Space heaters;
- Equipment used exclusively for steam cleaning;

Rule 402 (Nuisance). This rule specifies that a person may not discharge from any source whatsoever such quantities of air contaminants or other material which cause injury, detriment, nuisance, or annoyance to any considerable number of persons or to the public, or which endanger the comfort, repose, health, or safety of any such persons or the public, or which cause, or have a natural tendency to cause, injury or damage to business or property.

Rule 403.2 (Fugitive Dust Control for the Mojave Desert Planning Area). This rule requires owners or operators of a construction or demolition fugitive dust source to implement the fugitive dust control measures listed in Rule 403.2. These measures include periodic watering for short-term stabilization of disturbed surface area to minimize visible dust emissions, stabilization of graded surfaces if no development is planned within 30 days, reducing non-essential earth moving activity under high wind conditions, and more. In addition, for sites over 100 acres such as the proposed project, the control measures in Rule 403.2 must also be implemented. The additional control measures include preparing and submitting a dust control plan to the MDAQMD prior to commencing earth-moving activities. The dust control plan must describe all applicable dust control measures that will be implemented at the project site. Other additional control measures to minimize visible fugitive dust for sites over 100 acres include stabilizing access routes, maintaining natural topography to the extent possible, and constructing paved roads and parking lots first where feasible.

Rule 1113 (Architectural Coatings). This rule requires manufacturers, distributors, and end-users of architectural and industrial maintenance coatings to reduce VOC emissions from the use of these coatings, primarily by placing limits on the VOC content of various coating categories.

Rule 1160 (Internal Combustion Engines). This rule establishes limits for VOC, NOx, and CO emissions associated with stationary internal combustion engines. However, the provisions of the rule do not apply to the following engines:

- All internal combustion engines rated at less than 500 brake horsepower;
- All internal combustion engines operated less than 100 hours within any continuous four consecutive calendar quarter period; and
- Emergency internal combustion engines.

Regulation XIII (New Source Review). For new and modified stationary sources subject to permitting requirements (see Rule 201), this series of rules prescribes the use of Best Available Control Technology and the provision of emission offsets (i.e., mitigation) for equipment whose emissions exceed specified

thresholds. The applicability of these requirements would be determined upon submittal of an application for permit to construct under Rule 201.

2.1.3 City of Victorville

City of Victorville General Plan

The City of Victorville General Plan contains the following greenhouse gas related policies and programs that are applicable to the proposed project:

Goal #6: Good Air Quality Promote clear air with low pollutant concentrations that do not adversely affect respiratory health

Objective 6.1 Contribute to regional air quality plan attainment

Policy 6.1.1 Encourage planning and development activities, that reduce the number and length of single occupant automobile trips

Implementation Measure 6.1.1.2 Require dust abatement actions for all new construction and redevelopment projects.

Implementation Measure 6.1.1.3 Maintain parking standards that encourage and facilitate alternative transportation modes, including reduced parking standards for transit-oriented developments, mixed-use developments, and preferential parking for carpoolers.

Objective 6.2 Reduce health risks associated with air pollution

Policy 6.2.1 Encourage compliance with the California Air Resources Board (CARB) “Air Quality and Land Use Handbook: A Community Health Perspective”, which provides guidelines for siting new sensitive land uses in proximity to air pollutant emitting sources

Implementation Measure 6.2.1.1 Avoid siting new sensitive land uses within 500 feet of a freeway, urban roads with 100,000 vehicles/day, or rural roads with 50,000 vehicles/day.

Implementation Measure 6.2.1.2 Avoid siting new sensitive land uses within 1,000 feet of a distribution center (that accommodates more than 100 trucks per day, more than 40 trucks with operating transport refrigeration units [TRUs] per day, or where TRU operations exceed 300 hours per week).

Implementation Measure 6.2.1.3 Avoid siting new sensitive land uses within 1,000 feet of a major service and maintenance rail yard.

- Implementation Measure 6.2.1.4 Avoid siting new sensitive land uses within 300 feet of any dry cleaning operation. For operations with two or more machines, provide 500 feet. For operations with three or more machines, consult with the Mojave Desert Air District prior to placement.
- Implementation Measure 6.2.1.5 Avoid siting new sensitive land uses within 300 feet of a large gas station (defined as a facility with a throughput of 3.6 million gallons per year or greater). A 50 foot separation is recommended for typical gas dispensing facilities.

2.2 Greenhouse Gas Regulatory Setting

2.2.1 International

Many countries around the globe have made an effort to reduce GHGs since climate change is a global issue.

Intergovernmental Panel on Climate Change. In 1988, the United Nations and the World Meteorological Organization established the Intergovernmental Panel on Climate Change to assess the scientific, technical and socio-economic information relevant to understanding the scientific basis of risk of human-induced climate change, its potential impacts, and options for adaptation and mitigation.

United Nations. The United States participates in the United Nations Framework Convention on Climate Change (UNFCCC) (signed on March 21, 1994). Under the Convention, governments gather and share information on greenhouse gas emissions, national policies, and best practices; launch national strategies for addressing greenhouse gas emissions and adapting to expected impacts, including the provision of financial and technological support to developing countries; and cooperate in preparing for adaptation to the impacts of climate change.

The 2014 UN Climate Change Conference in Lima Peru provided a unique opportunity to engage all countries to assess how developed countries are implementing actions to reduce emissions.

Kyoto Protocol. The Kyoto Protocol is a treaty made under the UNFCCC and was the first international agreement to regulate GHG emissions. It has been estimated that if the commitments outlined in the Kyoto Protocol are met, global GHG emissions could be reduced by an estimated 5 percent from 1990 levels during the first commitment period of 2008 – 2012 (UNFCCC 1997). On December 8, 2012, the Doha Amendment to the Kyoto Protocol was adopted. The amendment includes: New commitments for Annex I Parties to the Kyoto Protocol who agreed to take on commitments in a second commitment period from 2013 – 2020; a revised list of greenhouse gases (GHG) to be reported on by Parties in the second commitment period; and Amendments to several articles of the Kyoto Protocol which specifically referenced issues pertaining to the first commitment period and which needed to be updated for the second commitment period.

The Paris Agreement. The Paris Agreement became effective on November 4, 2016. Thirty days after this date at least 55 Parties to the United Nations Framework Convention on Climate Change (Convention), accounting in total for at least an estimated 55 % of the total global greenhouse gas emissions, had deposited their instruments of ratification, acceptance, approval or accession with the Depository.

The Paris Agreement built upon the Convention and – for the first time – attempted to bring all nations into a common cause to undertake ambitious efforts to combat climate change and adapt to its effects, with enhanced support to assist developing countries to do so. As such, it charts a new course in the global climate effort.

The Paris Agreement’s central aim is to strengthen the global response to the threat of climate change by keeping a global temperature rise this century well below 2 degrees Celsius above pre-industrial levels and to pursue efforts to limit the temperature increase even further to 1.5 degrees Celsius. Additionally, the agreement aims to strengthen the ability of countries to deal with the impacts of climate change. To reach these ambitious goals, appropriate financial flows, a new technology framework and an enhanced capacity building framework will be put in place, thus supporting action by developing countries and the most vulnerable countries, in line with their own national objectives. The Agreement also provides for enhanced transparency of action and support through a more robust transparency framework.

2.2.2 National

Greenhouse Gas Endangerment. On December 2, 2009, the EPA announced that GHGs threaten the public health and welfare of the American people. The EPA also states that GHG emissions from on-road vehicles contribute to that threat. The decision was based on *Massachusetts v. EPA* (Supreme Court Case 05-1120) which argued that GHGs are air pollutants covered by the Clean Air Act and that the EPA has authority to regulate those emissions.

Clean Vehicles. Congress first passed the Corporate Average Fuel Economy law in 1975 to increase the fuel economy of cars and light duty trucks. The law has become more stringent over time. On May 19, 2009, President Obama put in motion a new national policy to increase fuel economy for all new cars and trucks sold in the United States. On April 1, 2010, the EPA and the Department of Transportation’s National Highway Safety Administration announced a joint final rule establishing a national program that would reduce greenhouse gas emissions and improve fuel economy for new cars and trucks sold in the United States.

The first phase of the national program would apply to passenger cars, light-duty trucks, and medium-duty passenger vehicles, covering model years 2012 through 2016. They require these vehicles to meet an estimated combined average emissions level of 250 grams of carbon dioxide per mile, equivalent to 35.5 miles per gallon if the automobile industry were to meet this carbon dioxide level solely through fuel economy improvements. Together, these standards would cut carbon dioxide emissions by an estimated 960 million metric tons and 1.8 billion barrels of oil over the lifetime of the vehicles sold under the program (model years 2012-2016). The second phase of the national program would involve

proposing new fuel economy and greenhouse gas standards for model years 2017 – 2025 by September 1, 2011.

On October 25, 2010, the EPA and the U.S. Department of Transportation proposed the first national standards to reduce greenhouse gas emissions and improve fuel efficiency of heavy-duty trucks and buses. For combination tractors, the agencies are proposing engine and vehicle standards that begin in the 2014 model year and achieve up to a 20 percent reduction in carbon dioxide emissions and fuel consumption by the 2018 model year. For heavy-duty pickup trucks and vans, the agencies are proposing separate gasoline and diesel truck standards, which phase in starting in the 2014 model year and achieve up to a 10 percent reduction for gasoline vehicles and 15 percent reduction for diesel vehicles by 2018 model year (12 and 17 percent respectively if accounting for air conditioning leakage). Lastly, for vocational vehicles, the agencies are proposing engine and vehicle standards starting in the 2014 model year which would achieve up to a 10 percent reduction in fuel consumption and carbon dioxide emissions by 2018 model year.

Issued by NHTSA and EPA in March 2020 (published on April 30, 2020 and effective after June 29, 2020), the Safer Affordable Fuel-Efficient Vehicles Rule would maintain the CAFE and CO₂ standards applicable in model year 2020 for model years 2021 through 2026. The estimated CAFE and CO₂ standards for model year 2020 are 43.7 mpg and 204 grams of CO₂ per mile for passenger cars and 31.3 mpg and 284 grams of CO₂ per mile for light trucks, projecting an overall industry average of 37 mpg, as compared to 46.7 mpg under the standards issued in 2012. This Rule also excludes CO₂- equivalent emission improvements associated with air conditioning refrigerants and leakage (and, optionally, offsets for nitrous oxide and methane emissions) after model year 2020.¹

Mandatory Reporting of Greenhouse Gases. On January 1, 2010, the EPA started requiring large emitters of heat-trapping emissions to begin collecting GHG data under a new reporting system. Under the rule, suppliers of fossil fuels or industrial greenhouse gases, manufacturers of vehicles and engines, and facilities that emit 25,000 metric tons or more per year of greenhouse gas emissions are required to submit annual reports to the EPA.

Climate Adaption Plan. The EPA Plan identifies priority actions the Agency will take to incorporate considerations of climate change into its programs, policies, rules and operations to ensure they are effective under future climatic conditions. The following link provides more information on the EPA Plan: <https://www.epa.gov/arc-x/planning-climate-change-adaptation>

Energy Independence Security Act

The Energy Independence and Security Act of 2007 (EISA) facilitates the reduction of national

¹ National Highway Traffic Safety Administration (NHTSA) and U.S. Environmental Protection Agency (USEPA), 2018. Federal Register / Vol. 83, No. 165 / Friday, August 24, 2018 / Proposed Rules, The Safer Affordable Fuel-Efficient (SAFE) Vehicles Rule for Model Years 2021-2026 Passenger Cars and Light Trucks 2018. Available at: <https://www.gpo.gov/fdsys/pkg/FR-2018-08-24/pdf/2018-16820.pdf>.

GHG emissions by requiring the following:

- Increasing the supply of alternative fuel sources by setting a mandatory Renewable Fuel Standard (RFS) that requires fuel producers to use at least 36 billion gallons of biofuel in 2022;
- Prescribing or revising standards affecting regional efficiency for heating and cooling products, procedures for new or amended standards, energy conservation, energy efficiency labeling for consumer electronic products, residential boiler efficiency, electric motor efficiency, and home appliances;
- Requiring approximately 25 percent greater efficiency for light bulbs by phasing out incandescent light bulbs between 2012 and 2014; requiring approximately 200 percent greater efficiency for light bulbs, or similar energy savings, by 2020; and
- While superseded by the USEPA and NHTSA actions described above, (i) establishing miles per gallon targets for cars and light trucks and (ii) directing the NHTSA to establish a fuel economy program for medium- and heavy-duty trucks and create a separate fuel economy standard for trucks.
- Additional provisions of EISA address energy savings in government and public institutions, promote research for alternative energy, additional research in carbon capture, international energy programs, and the creation of green jobs.²

Executive Order 13432

In response to the Massachusetts v. Environmental Protection Agency ruling, the President signed Executive Order 13432 on May 14, 2007, directing the USEPA, along with the Departments of Transportation, Energy, and Agriculture, to initiate a regulatory process that responds to the Supreme Court's decision. Executive Order 13432 was codified into law by the 2009 Omnibus Appropriations Law signed on February 17, 2009. The order sets goals in the areas of energy efficiency, acquisition, renewable energy, toxics reductions, recycling, sustainable buildings, electronics stewardship, fleets, and water conservation. Light-Duty Vehicle Greenhouse Gas and Corporate Average Fuel Economy Standards.

On May 19, 2009, President Obama announced a national policy for fuel efficiency and emissions standards in the United States auto industry. The adopted federal standard applies to passenger cars and light-duty trucks for model years 2012 through 2016. The rule surpasses the prior Corporate Average Fuel Economy standards (CAFE)³ and requires an average fuel economy standard of 35.5 miles per gallon (mpg) and 250 grams of CO₂ per mile by model year 2016, based on USEPA calculation methods. These

² A green job, as defined by the United States Department of Labor, is a job in business that produces goods or provides services that benefit the environment or conserve natural resources.

³ The Corporate Average Fuel Economy standards are regulations in the United States, first enacted by Congress in 1975, to improve the average fuel economy of cars and light trucks. The U.S Department of Transportation has delegated the National Highway Traffic Safety Administration as the regulatory agency for the Corporate Average Fuel Economy standards.

standards were formally adopted on April 1, 2010. In August 2012, standards were adopted for model year 2017 through 2025 for passenger cars and light-duty trucks. By 2025, vehicles are required to achieve 54.5 mpg (if GHG reductions are achieved exclusively through fuel economy improvements) and 163 grams of CO₂ per mile. According to the USEPA, a model year 2025 vehicle would emit one-half of the GHG emissions from a model year 2010 vehicle.⁴ In 2017, the USEPA recommended no change to the GHG standards for light-duty vehicles for model years 2022-2025.

In August 2018, the USEPA and NHTSA proposed the Safer Affordable Fuel-Efficient Vehicles Rule that would, if adopted, maintain the CAFE and CO₂ standards applicable in model year 2020 for model years 2021 through 2026. The estimated CAFE and CO₂ standards for model year 2020 are 43.7 mpg and 204 grams of CO₂ per mile for passenger cars and 31.3 mpg and 284 grams of CO₂ per mile for light trucks, projecting an overall industry average of 37 mpg, as compared to 46.7 mpg under the standards issued in 2012. The proposal, if adopted, would also exclude CO₂-equivalent emission improvements associated with air conditioning refrigerants and leakage (and, optionally, offsets for nitrous oxide and methane emissions) after model year 2020.⁵

2.2.3 California

California Code of Regulations (CCR) Title 24, Part 6. CCR Title 24, Part 6: California's Energy Efficiency Standards for Residential and Nonresidential Buildings (Title 24) were first established in 1978 in response to a legislative mandate to reduce California's energy consumption. The standards are updated periodically to allow consideration and possible incorporation of new energy efficiency technologies and methods. Although it was not originally intended to reduce GHG emissions, electricity production by fossil fuels results in GHG emissions and energy efficient buildings require less electricity. Therefore, increased energy efficiency results in decreased GHG emissions.

The Energy Commission adopted 2008 Standards on April 23, 2008 and Building Standards Commission approved them for publication on September 11, 2008. These updates became effective on August 1, 2009. 2013 and 2016 standards have been approved and became effective July 1, 2014 and January 1, 2016, respectively. 2019 standards were published July 1, 2019 and became effective January 1, 2020.

California Code of Regulations (CCR) Title 24, Part 11. All buildings for which an application for a building permit is submitted on or after January 1, 2023 must follow the 2022 standards. Energy efficient buildings require less electricity; therefore, increased energy efficiency reduces fossil fuel consumption

⁴ United States Environmental Protection Agency, EPA and NHTSA Set Standards to Reduce Greenhouse Gases and Improve Fuel Economy for Model Years 2017-2025 Cars and Light Trucks, August 2012, <https://nepis.epa.gov/Exe/ZyPDF.cgi/P100EZ7C.PDF?Dockey=P100EZ7C.PDF>.

⁵ National Highway Traffic Safety Administration (NHTSA) and U.S. Environmental Protection Agency (USEPA), 2018. Federal Register / Vol. 83, No. 165 / Friday, August 24, 2018 / Proposed Rules, The Safer Affordable Fuel-Efficient (SAFE) Vehicles Rule for Model Years 2021–2026 Passenger Cars and Light Trucks 2018. Available at <https://www.gpo.gov/fdsys/pkg/FR-2018-08-24/pdf/2018-16820.pdf>.

and decreases greenhouse gas emissions. The following links provide more information on Title 24, Part 11:

<https://www.dgs.ca.gov/BSC/Codes>

<https://www.energy.ca.gov/programs-and-topics/programs/building-energy-efficiency-standards/2022-building-energy-efficiency>

California Green Building Standards. On January 12, 2010, the State Building Standards Commission unanimously adopted updates to the California Green Building Standards Code, which went into effect on January 1, 2011. The Housing and Community Development (HCD) updated CALGreen through the 2015 Triennial Code Adoption Cycle, during the 2016 to 2017 fiscal year. During the 2022-2023 fiscal year, the Department of Housing and Community Development (HCD) updated CALGreen through the 2023 Triennial Code Adoption Cycle.

The Code is a comprehensive and uniform regulatory code for all residential, commercial and school buildings. CCR Title 24, Part 11: California Green Building Standards (Title 24) became effective in 2001 in response to continued efforts to reduce GHG emissions associated with energy consumption. CCR Title 24, Part 11 now require that new buildings reduce water consumption, employ building commissioning to increase building system efficiencies, divert construction waste from landfills, and install low pollutant-emitting finish materials. One focus of CCR Title 24, Part 11 is water conservation measures, which reduce GHG emissions by reducing electrical consumption associated with pumping and treating water. CCR Title 24, Part 11 has approximately 52 nonresidential mandatory measures and an additional 130 provisions for optional use. Some key mandatory measures for commercial occupancies include specified parking for clean air vehicles, a 20 percent reduction of potable water use within buildings, a 50 percent construction waste diversion from landfills, use of building finish materials that emit low levels of volatile organic compounds, and commissioning for new, nonresidential buildings over 10,000 square feet.

The CEC estimates that over 30 years the 2022 Energy Code will provide \$1.5 billion in consumer benefits and reduce 10 million metric tons of GHG. Changes compared to the 2019 Energy Code include increases to on-site renewable energy generation from solar, increases to electric load flexibility to support grid reliability, reduction of emissions from newly constructed buildings, reduction of air pollution for improved public health, and increased adoption of environmentally beneficial efficient electric technologies.

The California Green Building Standards Code does not prevent a local jurisdiction from adopting a more stringent code as state law provides methods for local enhancements. The Code recognizes that many jurisdictions have developed existing construction and demolition ordinances, and defers to them as the ruling guidance provided, they provide a minimum 50-percent diversion requirement. The code also provides exemptions for areas not served by construction and demolition recycling infrastructure. State building code provides the minimum standard that buildings need to meet in order to be certified for occupancy. Enforcement is generally through the local building official. The following link provides more on CalGreen Building Standards:

<http://www.bsc.ca.gov/Home/CALGreen.aspx>

Executive Order S-3-05. California Governor issued Executive Order S-3-05, GHG Emission, in June 2005, which established the following targets:

- By 2010, California shall reduce greenhouse gas emissions to 2000 levels;
- By 2020, California shall reduce greenhouse gas emissions to 1990 levels.
- By 2050, California shall reduce greenhouse gas emissions to 80 percent below 1990 levels.

The executive order directed the secretary of the California Environmental Protection Agency (CalEPA) to coordinate a multi-agency effort to reduce GHG emissions to the target levels. To comply with the Executive Order, the secretary of CalEPA created the California Climate Action Team (CAT), made up of members from various state agencies and commissions. The team released its first report in March 2006. The report proposed to achieve the targets by building on the voluntary actions of businesses, local governments, and communities and through State incentive and regulatory programs.

Executive Order S-01-07. Executive Order S-1-07 was issued in 2007 and proclaims that the transportation sector is the main source of GHG emissions in the State, since it generates more than 40 percent of the State's GHG emissions. It establishes a goal to reduce the carbon intensity of transportation fuels sold in the State by at least ten percent by 2020. This Order also directs CARB to determine whether this Low Carbon Fuel Standard (LCFS) could be adopted as a discrete early-action measure as part of the effort to meet the mandates in AB 32.

On April 23, 2009 CARB approved the proposed regulation to implement the low carbon fuel standard and began implementation on January 1, 2011. The low carbon fuel standard is anticipated to reduce GHG emissions by about 16 MMT per year by 2020. CARB approved some amendments to the LCFS in December 2011, which were implemented on January 1, 2013. In September 2015, the Board approved the re-adoption of the LCFS, which became effective on January 1, 2016, to address procedural deficiencies in the way the original regulation was adopted. In 2018, the Board approved amendments to the regulation, which included strengthening and smoothing the carbon intensity benchmarks through 2030 in-line with California's 2030 GHG emission reduction target enacted through SB 32, adding new crediting opportunities to promote zero emission vehicle adoption, alternative jet fuel, carbon capture and sequestration, and advanced technologies to achieve deep decarbonization in the transportation sector.

The LCFS is designed to encourage the use of cleaner low-carbon transportation fuels in California, encourage the production of those fuels, and therefore, reduce GHG emissions and decrease petroleum dependence in the transportation sector. Separate standards are established for gasoline and diesel fuels and the alternative fuels that can replace each. The standards are "back-loaded", with more reductions required in the last five years, than the first five years. This schedule allows for the development of advanced fuels that are lower in carbon than today's fuels and the market penetration of plug-in hybrid electric vehicles, battery electric vehicles, fuel cell vehicles, and flexible fuel vehicles. It is anticipated that compliance with the low carbon fuel standard will be based on a combination of both lower carbon fuels and more efficient vehicles.

Reformulated gasoline mixed with corn-derived ethanol at ten percent by volume and low sulfur diesel fuel represent the baseline fuels. Lower carbon fuels may be ethanol, biodiesel, renewable diesel, or blends of these fuels with gasoline or diesel as appropriate. Compressed natural gas and liquefied natural gas also may be low carbon fuels. Hydrogen and electricity, when used in fuel cells or electric vehicles are also considered as low carbon fuels for the low carbon fuel standard.

SB 97. Senate Bill 97 (SB 97) was adopted August 2007 and acknowledges that climate change is a prominent environmental issue that requires analysis under CEQA. SB 97 directed the Governor's Office of Planning and Research (OPR), which is part of the State Resource Agency, to prepare, develop, and transmit to CARB guidelines for the feasible mitigation of GHG emissions or the effects of GHG emissions, as required by CEQA, by July 1, 2009. The Resources Agency was required to certify and adopt those guidelines by January 1, 2010.

Pursuant to the requirements of SB 97 as stated above, on December 30, 2009 the Natural Resources Agency adopted amendments to the state CEQA guidelines that address GHG emissions. The CEQA Guidelines Amendments changed 14 sections of the CEQA Guidelines and incorporate GHG language throughout the Guidelines. However, no GHG emissions thresholds of significance are provided and no specific mitigation measures are identified. The GHG emission reduction amendments went into effect on March 18, 2010 and are summarized below:

- Climate action plans and other greenhouse gas reduction plans can be used to determine whether a project has significant impacts, based upon its compliance with the plan.
- Local governments are encouraged to quantify the greenhouse gas emissions of proposed projects, noting that they have the freedom to select the models and methodologies that best meet their needs and circumstances. The section also recommends consideration of several qualitative factors that may be used in the determination of significance, such as the extent to which the given project complies with state, regional, or local GHG reduction plans and policies. OPR does not set or dictate specific thresholds of significance. Consistent with existing CEQA Guidelines, OPR encourages local governments to develop and publish their own thresholds of significance for GHG impacts assessment.
- When creating their own thresholds of significance, local governments may consider the thresholds of significance adopted or recommended by other public agencies, or recommended by experts.
- New amendments include guidelines for determining methods to mitigate the effects of greenhouse gas emissions in Appendix F of the CEQA Guidelines.
- OPR is clear to state that "to qualify as mitigation, specific measures from an existing plan must be identified and incorporated into the project; general compliance with a plan, by itself, is not mitigation."
- OPR's emphasizes the advantages of analyzing GHG impacts on an institutional, programmatic level. OPR therefore approves tiering of environmental analyses and highlights some benefits of such an approach.
- Environmental impact reports (EIRs) must specifically consider a project's energy use and energy efficiency potential.

AB 32. The California State Legislature enacted AB 32, the California Global Warming Solutions Act of 2006. AB 32 requires that greenhouse gases emitted in California be reduced to 1990 levels by the year 2020. “Greenhouse gases” as defined under AB 32 include carbon dioxide, methane, nitrous oxide, hydrofluorocarbons, perfluorocarbons, and sulfur hexafluoride. ARB is the state agency charged with monitoring and regulating sources of greenhouse gases. AB 32 states the following:

Global warming poses a serious threat to the economic well-being, public health, natural resources, and the environment of California. The potential adverse impacts of global warming include the exacerbation of air quality problems, a reduction in the quality and supply of water to the state from the Sierra snowpack, a rise in sea levels resulting in the displacement of thousands of coastal businesses and residences, damage to marine ecosystems and the natural environment, and an increase in the incidences of infectious diseases, asthma, and other human health-related problems.

The ARB Board approved the 1990 greenhouse gas emissions level of 427 million metric tons of carbon dioxide equivalent (MMT_{CO2e}) on December 6, 2007 (California Air Resources Board 2007). Therefore, emissions generated in California in 2020 are required to be equal to or less than 427 MMT_{CO2e}. Emissions in 2020 in a “business as usual” scenario are estimated to be 596 MMT_{CO2e}.

Under AB 32, the ARB published its Final Expanded List of Early Action Measures to Reduce Greenhouse Gas Emissions in California. Discrete early action measures are currently underway or are enforceable by January 1, 2010. The ARB has 44 early action measures that apply to the transportation, commercial, forestry, agriculture, cement, oil and gas, fire suppression, fuels, education, energy efficiency, electricity, and waste sectors. Of these early action measures, nine are considered discrete early action measures, as they are regulatory and enforceable by January 1, 2010. The ARB estimates that the 44 recommendations are expected to result in reductions of at least 42 MMT_{CO2e} by 2020, representing approximately 25 percent of the 2020 target.

The ARB’s Climate Change Scoping Plan (Scoping Plan) contains measures designed to reduce the State’s emissions to 1990 levels by the year 2020 (California Air Resources Board 2008). The Scoping Plan identifies recommended measures for multiple greenhouse gas emission sectors and the associated emission reductions needed to achieve the year 2020 emissions target—each sector has a different emission reduction target. Most of the measures target the transportation and electricity sectors. As stated in the Scoping Plan, the key elements of the strategy for achieving the 2020 greenhouse gas target include:

- Expanding and strengthening existing energy efficiency programs as well as building and appliance standards;
- Achieving a statewide renewables energy mix of 33 percent;
- Developing a California cap-and-trade program that links with other Western Climate Initiative partner programs to create a regional market system;
- Establishing targets for transportation-related greenhouse gas emissions for regions throughout California and pursuing policies and incentives to achieve those targets;

- Adopting and implementing measures pursuant to existing State laws and policies, including California’s clean car standards, goods movement measures, and the Low Carbon Fuel Standard; and
- Creating targeted fees, including a public goods charge on water use, fees on high global warming potential gases, and a fee to fund the administrative costs of the State’s long-term commitment to AB 32 implementation.

In addition, the Scoping Plan differentiates between “capped” and “uncapped” strategies. “Capped” strategies are subject to the proposed cap-and-trade program. The Scoping Plan states that the inclusion of these emissions within the cap-and-trade program will help ensure that the year 2020 emission targets are met despite some degree of uncertainty in the emission reduction estimates for any individual measure. Implementation of the capped strategies is calculated to achieve a sufficient amount of reductions by 2020 to achieve the emission target contained in AB 32. “Uncapped” strategies that will not be subject to the cap-and-trade emissions caps and requirements are provided as a margin of safety by accounting for additional greenhouse gas emission reductions.⁴

Senate Bill 100. Senate Bill 100 (SB 100) requires 100 percent of total retail sales of electricity in California to come from eligible renewable energy resources and zero-carbon resources by December 31, 2045. SB 100 was adopted September 2018.

The interim thresholds from prior Senate Bills and Executive Orders would also remain in effect. These include Senate Bill 1078 (SB 1078), which requires retail sellers of electricity, including investor-owned utilities and community choice aggregators, to provide at least 20 percent of their supply from renewable sources by 2017. Senate Bill 107 (SB 107) which changed the target date to 2010. Executive Order S-14-08, which was signed on November 2008 and expanded the State’s Renewable Energy Standard to 33 percent renewable energy by 2020. Executive Order S-21-09 directed the CARB to adopt regulations by July 31, 2010 to enforce S-14-08. Senate Bill X1-2 codifies the 33 percent renewable energy requirement by 2020.

Senate Bill 350. Signed into law October 7, 2015, SB 350 increases California’s renewable electricity procurement goal from 33 percent by 2020 to 50 percent by 2030. This will increase the use of Renewables Portfolio Standard (RPS) eligible resources, including solar, wind, biomass, geothermal, and others. In addition, SB 350 requires the state to double statewide energy efficiency savings in electricity and natural gas end uses by 2030. To help ensure these goals are met and the greenhouse gas emission reductions are realized, large utilities will be required to develop and submit Integrated Resource Plans (IRPs). These IRPs will detail how each entity will meet their customers resource needs, reduce greenhouse gas emissions and ramp up the deployment of clean energy resources.

SB 375. Senate Bill 375 (SB 375) was adopted September 2008 and aligns regional transportation planning efforts, regional GHG emission reduction targets, and land use and housing allocation. SB 375 requires Metropolitan Planning Organizations (MPO) to adopt a sustainable communities strategy (SCS) or alternate planning strategy (APS) that will prescribe land use allocation in that MPOs Regional Transportation Plan (RTP). CARB, in consultation with each MPO, will provide each affected region with reduction targets for GHGs emitted by passenger cars and light trucks in the region for the years 2020

and 2035. These reduction targets will be updated every eight years but can be updated every four years if advancements in emissions technologies affect the reduction strategies to achieve the targets. CARB is also charged with reviewing each MPO's sustainable communities strategy or alternate planning strategy for consistency with its assigned targets.

The proposed project is located within the Southern California Association of Governments (SCAG), which has authority to develop the SCS or APS. For the SCAG region, the targets set by CARB are at eight percent below 2005 per capita GHG emissions levels by 2020 and 13 percent below 2005 per capita GHG emissions levels by 2035. On April 4, 2012, SCAG adopted the 2012-2035 Regional Transportation Plan / Sustainable Communities Strategy (RTP/SCS), which meets the CARB emission reduction requirements.

On September 3, 2020, SCAG's Regional Council approved and fully adopted the Connect SoCal (2020–2045 Regional Transportation Plan/Sustainable Communities Strategy), and the addendum to the Connect SoCal Program Environmental Impact Report. Connect SoCal is a long-range visioning plan that builds upon and expands land use and transportation strategies established over several planning cycles to increase mobility options and achieve a more sustainable growth pattern. Connect SoCal outlines more than \$638 billion in transportation system investments through 2045. Connect SoCal is supported by a combination of transportation and land use strategies that help the region achieve state greenhouse gas emission reduction goals and federal Clean Air Act requirements, preserve open space areas, improve public health and roadway safety, support our vital goods movement industry and utilize resources more efficiently. By integrating the Forecasted Development Pattern with a suite of financially constrained transportation investments, Connect SoCal can reach the regional target of reducing greenhouse gases, or GHGs, from autos and light-duty trucks by 8 percent per capita by 2020, and 19 percent by 2035 (compared to 2005 levels).

City and County land use policies, including General Plans, are not required to be consistent with the RTP and associated SCS or APS. However, new provisions of CEQA would incentivize, through streamlining and other provisions, qualified projects that are consistent with an approved SCS or APS and categorized as "transit priority projects."

Senate Bill X7-7. Senate Bill X7-7 (SB X7-7), enacted on November 9, 2009, mandates water conservation targets and efficiency improvements for urban and agricultural water suppliers. SB X7-7 requires the Department of Water Resources (DWR) to develop a task force and technical panel to develop alternative best management practices for the water sector. In addition, SB X7-7 required the DWR to develop criteria for baseline uses for residential, commercial, and industrial uses for both indoor and landscaped area uses. The DWR was also required to develop targets and regulations that achieve a statewide 20 percent reduction in water usage.

Assembly Bill 939, Assembly Bill 341, and Senate Bill 1374. Assembly Bill 939 (AB 939) requires that each jurisdiction in California to divert at least 50 percent of its waste away from landfills, whether through waste reduction, recycling or other means. AB 341 requires at least 75 percent of generated waste be source reduced, recycled, or composted by the year 2020. Senate Bill 1374 (SB 1374) requires the California Integrated Waste Management Board to adopt a model ordinance by March 1, 2004

suitable for adoption by any local agency to require 50 to 75 percent diversion of construction and demolition of waste materials from landfills.

Executive Order S-13-08. Executive Order S-13-08 indicates that “climate change in California during the next century is expected to shift precipitation patterns, accelerate sea level rise and increase temperatures, thereby posing a serious threat to California’s economy, to the health and welfare of its population and to its natural resources.” Pursuant to the requirements in the order, the 2009 California Climate Adaptation Strategy (California Natural Resource Agency 2009) was adopted, which is the “... first statewide, multi-sector, region-specific, and information-based climate change in California, identifying and exploring strategies to adapt to climate change, and specifying a direction for future research.

Executive Order B-30-15. Executive Order B-30-15, establishing a new interim statewide greenhouse gas emission reduction target to reduce greenhouse gas emissions to 40 percent below 1990 levels by 2030, was signed by Governor Brown in April 2015.

Executive Order B-29-15. Executive Order B-29-15, mandates a statewide 25% reduction in potable water usage and was signed into law on April 1, 2015.

Executive Order B-37-16. Executive Order B-37-16, continuing the State’s adopted water reduction, was signed into law on May 9, 2016. The water reduction builds off the mandatory 25% reduction called for in EO B-29-15.

Executive Order N-79-20. Executive Order N-79-20 was signed into law on September 23, 2020 and mandates 100 percent of in-state sales of new passenger cars and trucks be zero-emission by 2035; 100 percent of medium- and heavy-duty vehicles in the state be zero-emission vehicles by 2045 for all operations where feasible and by 2035 for drayage trucks; and to transition to 100 percent zero-emission off-road vehicles and equipment by 2035 where feasible.

SBX1 2. Signed into law in April 2011, SBX1 2, requires one-third of the State’s electricity to come from renewable sources. The legislation increases California’s current 20 percent renewables portfolio standard target in 2010 to a 33 percent renewables portfolio standard by December 31, 2020.

2.2.4 Mojave Desert Air Quality Management District

The project is within the MDAB, which is under the jurisdiction of the MDAQMD.

As shown in Table 3, the MDAQMD has identified thresholds of 100,000 tons per year or 548,000 pounds per day of CO₂e emissions for individual projects.

Table 3: MDAQMD Air Quality Significance Thresholds

Pollutant	Annual Thresholds (tons/year)	Daily Thresholds (pounds/day)
-----------	----------------------------------	----------------------------------

NOx	25	137
VOC	25	137
PM10	15	82
PM2.5	15	82
SOx	25	137
CO	100	548
Lead	0.6	3
Greenhouse Gases (CO2e)	100,000	548,000

Source: <http://www.mdaqmd.ca.gov/Modules/ShowDocument.aspx?documentid=2910>

2.2.5 City of Victorville

City of Victorville General Plan

The City of Victorville General Plan contains the following greenhouse gas related policies and programs that are applicable to the proposed project:

Goal #7: Energy Conservation Promote energy sustainability by developing alternative power supplies and reducing energy use

Objective 7.2 Promote energy conservation

Policy 7.2.1 Support energy conservation by requiring sustainable building design and development for new residential, commercial and industrial projects.

Implementation Measure 7.2.1.1 Incorporate green building principles and practices, to the extent practicable and financially feasible, into the design, development and operation of all City owned facilities.

Implementation Measure 7.2.1.2 Minimize energy use of new residential, commercial and industrial projects by requiring high efficiency heating, lighting and other appliances, such as cooking equipment, refrigerators, furnaces, overhead and area lighting, and low NOx water heaters

3.0 Setting

3.1 Existing Physical Setting

The project site is located approximately two miles north of the City of Victorville in the County of San Bernardino, which is part of the Mojave Desert Air Basin (MDAB) that includes the desert portion of San Bernardino County and the far eastern end of Riverside County

3.1.1 Local Climate and Meteorology

The MDAB is an assemblage of mountain ranges interspersed with long broad valleys that often contain dry lakes. Many of the lower mountains which dot the vast terrain rise from 1,000 to 4,000 feet above the valley floor. Prevailing winds in the MDAB are out of the west and southwest. These prevailing winds are due to the proximity of the MDAB to coastal and central regions and the blocking nature of the Sierra Nevada Mountains to the north; air masses pushed onshore in southern California by differential heating are channeled through the MDAB. The MDAB is separated from the southern California coastal and central California valley regions by mountains (highest elevation approximately 10,000 feet), whose passes form the main channels for these air masses. The Antelope Valley is bordered in the northwest by the Tehachapi Mountains, separated from the Sierra Nevada's in the north by the Tehachapi Pass (3,800-foot elevation). The Antelope Valley is bordered in the south by the San Gabriel Mountains, bisected by Soledad Canyon (3,300 feet). The Mojave Desert is bordered in the southwest by the San Bernardino Mountains, separated from the San Gabriel's by the Cajon Pass (4,200 feet). A lesser channel lies between the San Bernardino Mountains and the Little San Bernardino Mountains (the Morongo Valley).

The Palo Verde Valley portion of the Mojave Desert lies in the low desert, at the eastern end of a series of valleys (notably the Coachella Valley) whose primary channel is the San Gorgonio Pass (2,300 feet) between the San Bernardino and San Jacinto Mountains.

During the summer the MDAB is generally influenced by a Pacific Subtropical High cell that sits off the coast, inhibiting cloud formation and encouraging daytime solar heating. The MDAB is rarely influenced by cold air masses moving south from Canada and Alaska, as these frontal systems are weak and diffuse by the time they reach the desert. Most desert moisture arrives from infrequent warm, moist and unstable air masses from the south. The MDAB averages between three and seven inches of precipitation per year (from 16 to 30 days with at least 0.01 inches of precipitation). The MDAB is classified as a dry-hot desert climate (BWh), with portions classified as dry-very hot desert (BWbh), to indicate at least three months have maximum average temperatures over 100.4° F.

The temperature and precipitation levels for Victorville are in Table 4. Table 4 shows that July is typically the warmest month and December is typically the coolest month. Rainfall in the project area varies considerably in both time and space. Almost all the annual rainfall comes from the fringes of mid-latitude storms from late November to early April, with summers being almost completely dry.

Table 4: Meteorological Summary

Month	Temperature (°F)		Average Precipitation (inches)
	Average High	Average Low	
January	58.8	29.8	0.95
February	62.1	33.1	1.05
March	67.0	36.6	0.80
April	74.2	41.5	0.36
May	82.7	47.9	0.13
June	91.6	54.3	0.04
July	98.1	60.8	0.14
August	97.2	60.2	0.21
September	91.3	54.1	0.23
October	80.2	44.4	0.32
November	67.3	34.5	0.50
December	59.4	29.2	0.79
Annual Average	77.5	43.9	5.5
Notes: ¹ Source : https://wrcc.dri.edu/cgi-bin/cliMAIN.pl?ca4405			

3.1.2 Local Air Quality

The MDAQMD maintains an air-monitoring network that measures levels of several air pollutants throughout the air basin. Since not all air monitoring stations measure all of the tracked pollutants, the data from the following two monitoring stations, listed in the order of proximity to the project site have been used. The nearest air monitoring stations to the project site with available data is the Victorville monitoring station (Victorville Station) located approximately 2 miles southwest of the project site at 14306 Park Avenue. Table 5 presents the monitored pollutant levels within the vicinity. However, it should be noted that due to the air monitoring station distance from the project site, recorded air pollution levels at the air monitoring station reflect with varying degrees of accuracy, local air quality conditions at the project site.

<Table 5, next page>

Table 5: Local Area Air Quality Levels

Pollutant (Standard) ²	Year		
	2020	2021	2022
Ozone:			
Maximum 1-Hour Concentration (ppm)	0.112	0.112	0.100
Days > CAAQS (0.09 ppm)	4	8	3
Maximum 8-Hour Concentration (ppm)	0.094	0.098	0.090
Days > NAAQS (0.07 ppm)	35	34	44
Days > CAAQS (0.070 ppm)	38	35	49
Carbon Monoxide:			
Maximum 8-Hour Concentration (ppm)	*	*	*
Days > NAAQS (9 ppm)	0	0	0
Nitrogen Dioxide:			
Maximum 1-Hour Concentration (ppm)	0.059	0.057	0.054
Days > NAAQS (0.25 ppm)	0	0	0
Inhalable Particulates (PM10):			
Maximum 24-Hour Concentration (µg/m ³)	261.4	591.6	372.1
Days > NAAQS (150 µg /m ³)	1.9	1	2.1
Days > CAAQS (50 µg /m ³)	*	*	*
Annual Average (ug/m ³)	34.0	33.9	33.6
Annual > NAAQS (50 µg /m ³)	No	No	No
Annual > CAAQS (20 µg /m ³)	Yes	Yes	Yes
Ultra-Fine Particulates (PM2.5):			
Maximum 24-Hour Concentration (µg /m ³)	48.4	87.1	24.6
Days > NAAQS (35 µg /m ³)	4	1	0
Annual Average (µg /m ³)	9.7	10.2	8.9
Annual > NAAQS (15 µg /m ³)	No	No	No
Annual > CAAQS (12 µg /m ³)	No	No	No
¹ Source: obtained from https://www.arb.ca.gov/adam/topfour/topfour1.php ² CAAQS = California Ambient Air Quality Standard; NAAQS = National Ambient Air Quality Standard; ppm = parts per million; µg/m ³ = micrograms/cubic meter ³ No data available.			

The monitoring data presented in Table 5 shows that ozone and particulate matter (PM10) are the air pollutants of primary concern in the project area, which are detailed below.

Ozone

During the 2020 to 2022 monitoring period, the State 1-hour concentration standard for ozone were exceeded between 3 and 8 days each year at the Victorville Station. The State 8-hour ozone standard has been exceeded between 35 and 49 days each year over the past three years at the Victorville Station. The Federal 8-hour ozone standard has been exceeded between 34 and 44 days each year of the past three years at the Victorville Station.

Carbon Monoxide

CO is another important pollutant that is due mainly to motor vehicles. The Victorville Station did not record an exceedance of the state or federal 8-hour CO standards for the last three years.

Nitrogen Dioxide

The Victorville Station did not record an exceedance of the State or Federal NO₂ standards for the last three years.

Particulate Matter

During the 2020 to 2022 monitoring period, the Federal 24-hour standards for PM₁₀ have been exceeded between 1 and 2.1 days each year at the Victorville Station.

The Federal 24-hour standard for PM_{2.5} were exceeded 4 days in 2020 and 1 day in 2021 at the Victorville Station.

According to the EPA, some people are much more sensitive than others to breathing fine particles (PM₁₀ and PM_{2.5}). People with influenza, chronic respiratory and cardiovascular diseases, and the elderly may suffer worsening illness and premature death due to breathing these fine particles. People with bronchitis can expect aggravated symptoms from breathing in fine particles. Children may experience decline in lung function due to breathing in PM₁₀ and PM_{2.5}. Other groups considered sensitive are smokers and people who cannot breathe well through their noses. Exercising athletes are also considered sensitive, because many breathe through their mouths during exercise.

3.1.3 Attainment Status

The EPA and the ARB designate air basins where ambient air quality standards are exceeded as “nonattainment” areas. If standards are met, the area is designated as an “attainment” area. If there is inadequate or inconclusive data to make a definitive attainment designation, they are considered “unclassified.” National nonattainment areas are further designated as marginal, moderate, serious, severe, or extreme as a function of deviation from standards. Each standard has a different definition, or ‘form’ of what constitutes attainment, based on specific air quality statistics. For example, the Federal 8-hour CO standard is not to be exceeded more than once per year; therefore, an area is in attainment of the CO standard if no more than one 8-hour ambient air monitoring values exceeds the threshold per year. In contrast, the federal annual PM_{2.5} standard is met if the three-year average of the annual average PM_{2.5} concentration is less than or equal to the standard. Table 6 lists the attainment status for the criteria pollutants in the basin.

As indicated below in Table 3, the MDAB has been designated by the EPA as a non-attainment area for ozone (O₃) and suspended particulates (PM₁₀). Currently, the Basin is in attainment with the ambient air quality standards for carbon monoxide (CO), lead, sulfur dioxide (SO₂), nitrogen dioxide (NO₂) and particulate matter (PM_{2.5}).

<Table 6, next page>

Table 6: Attainment Status of MDAQMD¹ – Portion of Mojave Desert Air Basin

Pollutant	Federal Designation	State Designation
1-Hour Ozone	--	Nonattainment
8-Hour Ozone	Nonattainment	Nonattainment
CO	Unclassified/Attainment	Attainment
PM10	Nonattainment	Nonattainment
PM2.5	Unclassified/Attainment	Nonattainment
Lead	Unclassified/Attainment	Attainment
SO2	Unclassified/Attainment	Attainment
NO2	Unclassified/Attainment	Attainment
Notes:		
¹ MDAQMD = Mojave Desert Air Quality Management District		
² Source: California Air Resources Board (2019) (https://ww2.arb.ca.gov/resources/documents/maps-state-and-federal-area-designations) and MDAQMD (https://www.mdaqmd.ca.gov/air-quality/mdaqmd-attainment-status).		

3.2 Greenhouse Gases

Constituent gases of the Earth’s atmosphere, called atmospheric greenhouse gases (GHG), play a critical role in the Earth’s radiation amount by trapping infrared radiation emitted from the Earth’s surface, which otherwise would have escaped to space. Prominent greenhouse gases contributing to this process include carbon dioxide (CO₂), methane (CH₄), ozone, water vapor, nitrous oxide (N₂O), and chlorofluorocarbons (CFCs). This phenomenon, known as the Greenhouse Effect, is responsible for maintaining a habitable climate. Anthropogenic (caused or produced by humans) emissions of these greenhouse gases in excess of natural ambient concentrations are responsible for the enhancement of the Greenhouse Effect and have led to a trend of unnatural warming of the Earth’s natural climate, known as global warming or climate change. Emissions of gases that induce global warming are attributable to human activities associated with industrial/manufacturing, agriculture, utilities, transportation, and residential land uses. Transportation is responsible for 41 percent of the State’s greenhouse gas emissions, followed by electricity generation. Emissions of CO₂ and nitrous oxide (NO₂) are byproducts of fossil fuel combustion. Methane, a potent greenhouse gas, results from off-gassing associated with agricultural practices and landfills. Sinks of CO₂, where CO₂ is stored outside of the atmosphere, include uptake by vegetation and dissolution into the ocean. Table 7 provides a description of each of the greenhouse gases and their global warming potential.

Additional information is available: <https://www.arb.ca.gov/cc/inventory/data/data.htm>

<Table 7 on next page>

Table 7: Description of Greenhouse Gases

Greenhouse Gas	Description and Physical Properties	Sources
Nitrous oxide	Nitrous oxide (N ₂ O), also known as laughing gas is a colorless gas. It has a lifetime of 114 years. Its global warming potential is 298.	Microbial processes in soil and water, fuel combustion, and industrial processes. In addition to agricultural sources, some industrial processes (nylon production, nitric acid production) also emit N ₂ O.
Methane	Methane (CH ₄) is a flammable gas and is the main component of natural gas. It has a lifetime of 12 years. Its global warming potential is 25.	A natural source of CH ₄ is from the decay of organic matter. Methane is extracted from geological deposits (natural gas fields). Other sources are from the decay of organic material in landfills, fermentation of manure, and cattle farming.
Carbon dioxide	Carbon dioxide (CO ₂) is an odorless, colorless, natural greenhouse gas. Carbon dioxide's global warming potential is 1. The concentration in 2005 was 379 parts per million (ppm), which is an increase of about 1.4 ppm per year since 1960.	Natural sources include decomposition of dead organic matter; respiration of bacteria, plants, animals, and fungus; evaporation from oceans; and volcanic outgassing. Anthropogenic sources are from burning coal, oil, natural gas, and wood.
Chlorofluorocarbons	CFCs are nontoxic, nonflammable, insoluble, and chemically unreactive in the troposphere (the level of air at the earth's surface). They are gases formed synthetically by replacing all hydrogen atoms in methane or methane with chlorine and/or fluorine atoms. Global warming potentials range from 3,800 to 8,100.	Chlorofluorocarbons were synthesized in 1928 for use as refrigerants, aerosol propellants, and cleaning solvents. They destroy stratospheric ozone; therefore, their production was stopped as required by the Montreal Protocol.
Hydrofluorocarbons	Hydrofluorocarbons (HFCs) are a group of greenhouse gases containing carbon, chlorine, and at least one hydrogen atom. Global warming potentials range from 140 to 11,700.	Hydrofluorocarbons are synthetic manmade chemicals used as a substitute for chlorofluorocarbons in applications such as automobile air conditioners and refrigerants.
Perfluorocarbons	Perfluorocarbons (PFCs) have stable molecular structures and only break down by ultraviolet rays about 60 kilometers above the Earth's surface. They have a lifetime 10,000 to 50,000 years. They have a global warming potential range of 6,200 to 9,500.	Two main sources of perfluorocarbons are primary aluminum production and semiconductor manufacturing.
Sulfur hexafluoride	Sulfur hexafluoride (SF ₆) is an inorganic, odorless, colorless, and nontoxic, nonflammable gas. It has a lifetime of 3,200 years. It has a high global warming potential, 23,900.	This gas is manmade and used for insulation in electric power transmission equipment, in the magnesium industry, in semiconductor manufacturing, and as a tracer gas for leak detection.
Notes: 1. Sources: Intergovernmental Panel on Climate Change 2014a and Intergovernmental Panel on Climate Change 2014b. https://www.ipcc.ch/publications_and_data/ar4/wg1/en/ch2s2-10-2.html		

4.0 Modeling Parameters and Assumptions

4.1 Construction

Emissions are estimated using the CalEEMod (Version 2022.1.1.29) software, which is a statewide land use emissions computer model designed to provide a uniform platform for government agencies, land use planners, and environmental professionals to quantify potential criteria pollutant and GHG emissions from a variety of land use projects. CalEEMod was developed in collaboration with the air districts of California. Regional data (e.g., emission factors, trip lengths, meteorology, source inventory, etc.) have been provided by the various California air districts to account for local requirements and conditions. The model is considered to be an accurate and comprehensive tool for quantifying air quality and GHG impacts from land use projects throughout California.

The CalEEMod program uses the EMFAC2021 computer program to calculate the emission rates specific for the MDAQMD portion of San Bernardino County for construction-related employee vehicle trips and the OFFROAD2017 computer program to calculate emission rates for heavy truck operations. EMFAC2021 and OFFROAD2017 are computer programs generated by CARB that calculates composite emission rates for vehicles. Emission rates are reported by the program in grams per trip and grams per mile or grams per running hour. Using CalEEMod, the peak daily air pollutant emissions were calculated and presented below. These emissions represent the highest level of emissions for each of the construction phases in terms of air pollutant emissions.

The analysis assesses the emissions associated with the construction of the proposed project as indicated in Table 1. Per the site plan, the overall area to be disturbed during construction of the proposed project was estimated to be approximately 13.63 acres. Construction is estimated to occur over approximately 19 months beginning September 2025. The phases of the construction activities which have been analyzed below are: 1) site preparation, 2) grading, 3) building, 4) paving, and 5) architectural coating. For details on construction modeling and construction equipment for each phase, please see Appendix A.

4.2 Operations

Operational or long-term emissions occur over the life of the Project. Both mobile and area sources generate operational emissions. Area source emissions arise from consumer product usage, heaters that consume natural gas, gasoline-powered landscape equipment, and architectural coatings (painting). Mobile source emissions from motor vehicles are the largest single long-term source of air pollutants from the operation of the Project. Small amounts of emissions would also occur from area sources such as the consumption of natural gas for heating, hearths, from landscaping emissions, and consumer product usage. The operational emissions were estimated using the latest version of CalEEMod.

Mobile Sources

Mobile sources include emissions from the additional vehicle miles generated from the proposed project. The project will generate approximately 359 trips per day. The program then applies the emission factors for each trip which is provided by the EMFAC2021 model to determine the vehicular

traffic pollutant emissions. The CalEEMod default trip lengths were used in this analysis. Please see CalEEMod output comments sections in Appendix A for details.

Area Sources

Area sources include emissions from consumer products, landscape equipment and architectural coatings. Landscape maintenance includes fuel combustion emissions from equipment such as lawn mowers, rototillers, shredders/grinders, blowers, trimmers, chain saws, and hedge trimmers, as well as air compressors, generators, and pumps. As specifics were not known about the landscaping equipment fleet, CalEEMod defaults were used to estimate emissions from landscaping equipment.

Per MDAQMD Rule 1113 as amended on April 23, 2012, the architectural coatings that would be applied after January 1, 2013 will be limited to an average of 150 grams per liter or less.

Energy Usage

2022.1.1.29 CalEEMod defaults were utilized.

5.0 Thresholds of Significance

5.1 Air Quality Thresholds of Significance

5.1.1 CEQA Guidelines for Air Quality

The CEQA Guidelines define a significant effect on the environment as “a substantial, or potentially substantial, adverse change in the environment.” To determine if a project would have a significant impact on air quality, the type, level, and impact of emissions generated by the project must be evaluated.

The following air quality significance thresholds are contained in Appendix G of the CEQA Guidelines. A significant impact would occur if the project would:

- Conflict with or obstruct implementation of the applicable air quality plan;
- Result in a cumulatively considerable net increase of any criteria pollutant for which the project region is nonattainment under an applicable national or state ambient air quality standard;
- Expose sensitive receptors to substantial pollutant concentrations; or
- Result in other emissions (such as those leading to odors) adversely affecting a substantial number of people.

The CEQA Guidelines Section 15064.7 provides the significance criteria established by the applicable air quality management district or air pollution control district, when available, may be relied upon to make determinations of significance. The potential air quality impacts of the project are, therefore, evaluated according to thresholds developed by MDAQMD in their CEQA Guidelines.

5.1.2 Regional Significance Thresholds

According to the MDAQMD, a project is non-conforming if it conflicts with or delays implementation of any applicable attainment or maintenance plan. A project is conforming if it complies with all applicable MDAQMD rules and regulations, complies with all proposed control measures that are not yet adopted from the applicable plan(s), and it is consistent with the growth forecasts in the applicable plan(s) (or is directly included in the applicable plan).

Violation of Air Quality Standards or Substantial Contribution to Air Quality Violations. The MDAQMD currently recommends that projects with construction-related and/or operational emissions that exceed any of the following emissions thresholds should be considered significant:

- 25 tons per year or 137 pounds per day of VOC
- 25 tons per year or 137 pounds per day of NO_x
- 100 tons per year or 548 pounds per day of CO
- 25 tons per year or 137 pounds per day of SO_x
- 15 tons per year or 82 pounds per day of PM₁₀
- 12 tons per year or 65 pounds per day of PM_{2.5}

For the purposes to this air quality impact analysis, a regional air quality impact would be considered significant if emissions exceed the MDAQMD significance thresholds identified above and in Table 5.

5.2 Greenhouse Gas Thresholds of Significance

5.2.1 CEQA Guidelines for Greenhouse Gas

CEQA Guidelines define a significant effect on the environment as “a substantial, or potentially substantial, adverse change in the environment.” To determine if a project would have a significant impact on greenhouse gases, the type, level, and impact of emissions generated by the project must be evaluated.

The following greenhouse gas significance thresholds are contained in Appendix G of the CEQA Guidelines, which were amendments adopted into the Guidelines on March 18, 2010, pursuant to SB 97. A significant impact would occur if the project would:

- (a) Generate greenhouse gas emissions, either directly or indirectly, that may have a significant impact on the environment; or
- (b) Conflict with any applicable plan, policy or regulation of an agency adopted for the purpose of reducing the emissions of greenhouse gases.

However, despite this, currently neither the CEQA statutes, OPR guidelines, nor the draft proposed changes to the CEQA Guidelines prescribe thresholds of significance or a particular methodology for performing an impact analysis; as with most environmental topics, significance criteria are left to the judgment and discretion of the Lead Agency. As previously discussed (see Section 2.2.4 of this report), MDAQMD has identified thresholds of 100,000 tons per year or 548,000 pounds per day of CO₂e emissions for individual projects. The MDAQMD thresholds were used in this analysis. The project’s emissions will also be compared to a screening threshold of 3,000 MTCO₂e/year and the project is expected to comply with the performance standards for residential uses, as detailed in the *County of San Bernardino Greenhouse Gas Emissions Reduction Plan*.

6.0 Air Quality Emissions Impact

6.1 Construction Air Quality Emissions Impact

The latest version of CalEEMod was used to estimate the onsite and offsite construction emissions. The emissions incorporate Rule 403.2. Rule 403.2 (fugitive dust) is not considered a mitigation measure as the project by default is required to incorporate this rule during construction.

6.1.1 Regional Construction Emissions

The construction emissions for the project would not exceed MDAQMD’s daily and annual emissions thresholds as demonstrated in Table 8 and therefore would be considered less than significant.

Table 8: Regional Significance - Construction Emissions

Activity	Pollutant Emissions (pounds/day)					
	VOC	NOx	CO	SO ₂	PM10	PM2.5
Daily Emissions (pounds/day)						
2025	3.41	31.70	31.60	0.05	9.26	5.25
2026	1.56	10.80	20.80	0.03	1.81	0.69
2027	12.90	0.91	2.54	0.00	0.28	0.08
Maximum	12.90	31.70	31.60	0.05	9.26	5.25
MDAQMD Thresholds	137	137	548	137	82	65
Exceeds Thresholds	No	No	No	No	No	No
Annual Emissions (tons/year)						
2025	0.09	0.82	0.88	0.00	0.16	0.08
2026	0.20	1.42	2.47	0.00	0.24	0.09
2027	0.21	0.30	0.52	0.00	0.05	0.02
Total	0.50	2.54	3.87	0.00	0.45	0.19
MDAQMD Thresholds	25	25	100	25	15	12
Exceeds Thresholds	No	No	No	No	No	No
Notes:						
¹ Source: CalEEMod Version 2022.1.1.29						
² On-site emissions from equipment operated on-site that is not operated on public roads. On-site grading PM-10 and PM-2.5 emissions show mitigated values for fugitive dust for compliance with MDAQMD Rule 403.						
³ Off-site emissions from equipment operated on public roads.						
⁴ Construction, architectural coatings and paving phases may overlap.						

6.1.3 Odors

Potential sources that may emit odors during construction activities include the application of materials such as asphalt pavement. The objectionable odors that may be produced during the construction process are of short-term in nature and the odor emissions are expected cease upon the drying or hardening of the odor producing materials. Diesel exhaust and VOCs would be emitted during construction of the project, which are objectionable to some; however, emissions would disperse rapidly from the project site and therefore should not reach an objectionable level at the nearest sensitive receptors. Due to the short-term nature and limited amounts of odor producing materials being utilized, no significant impact related to odors would occur during construction of the proposed project.

6.1.4 Construction-Related Toxic Air Contaminant Impact

The greatest potential for toxic air contaminant emissions would be related to diesel particulate emissions associated with heavy equipment operations during construction of the proposed project. The Office of Environmental Health Hazard Assessment (OEHHA) has issued the Air Toxic Hot Spots Program Risk Assessment Guidelines and Guidance Manual for the Preparation of Health Risk Assessments, February 2015 to provide a description of the algorithms, recommended exposure variates, cancer and noncancer health values, and the air modeling protocols needed to perform a health risk assessment (HRA) under the Air Toxics Hot Spots Information and Assessment Act of 1987. Hazard identification includes identifying all substances that are evaluated for cancer risk and/or non-cancer acute, 8-hour, and chronic health impacts. In addition, identifying any multi-pathway substances that present a cancer risk or chronic non-cancer hazard via non-inhalation routes of exposure.

Given the relatively limited number of heavy-duty construction equipment and construction schedule, the proposed project would not result in a long-term substantial source of toxic air containment emissions and corresponding individual cancer risk. Furthermore, construction-based particulate matter (PM) emissions (including diesel exhaust emissions) do not exceed any regional thresholds. Therefore, no significant short-term toxic air contaminant impacts would occur during construction of the proposed project.

6.2 Operational Air Quality Emissions Impact

6.2.1 Regional Operational Emissions

The operations-related criteria air quality impacts created by the proposed project have been analyzed through the use of CalEEMod model. The operating emissions were based on year 2027, which is a conservative estimate of the opening year for the project. The summer and winter emissions created by the proposed project's long-term operations were calculated and the highest emissions from either summer or winter are summarized in Table 9.

<Table 9, next page>

Table 9: Regional Significance - Operational Emissions

Activity	Pollutant Emissions (tons/year) ¹					
	VOC	NOx	CO	SO2	PM10	PM2.5
Daily Emissions (pounds/day)						
Area Sources ²	1.67	0.07	7.83	0.00	0.00	0.00
Energy Usage ³	0.02	0.38	0.16	0.00	0.03	0.03
Mobile Sources ⁴	1.52	1.05	8.67	0.02	1.60	0.42
Total Emissions	3.21	1.50	16.66	0.02	1.63	0.45
MDAQMD Annual Thresholds	137	137	548	137	82	65
Exceeds Threshold?	No	No	No	No	No	No
Annual Emissions (tons/year)						
Area Sources ²	0.24	0.01	0.71	0.00	0.00	0.00
Energy Usage ³	0.00	0.07	0.03	0.00	0.01	0.01
Mobile Sources ⁴	0.24	0.19	1.39	0.00	0.29	0.08
Total Emissions	0.48	0.27	2.13	0.00	0.30	0.09
MDAQMD Annual Thresholds	25	25	100	25	15	12
Exceeds Threshold?	No	No	No	No	No	No
Notes:						
¹ Source: CalEEMod Version 2022.1.1.29						
² Area sources consist of emissions from consumer products, architectural coatings, and landscaping equipment.						
³ Energy usage consists of emissions from on-site natural gas usage.						
⁴ Mobile sources consist of emissions from vehicles and road dust.						

Table 9 provides the project's unmitigated operational emissions. Table 9 shows that the project does not exceed the MDAQMD regional emissions thresholds. Therefore, operational emissions are considered to be less than significant.

6.2.2 Operations-Related Toxic Air Contaminant Impacts

MDAQMD recommends avoiding siting new sensitive land uses such as residences, schools, daycare centers, playgrounds, or medical facilities within 1,000 feet of a major transportation project (50,000 or more vehicles per day).

The proposed project involves the construction of a behavioral health treatment campus and would be considered a sensitive receptor. The project would be located over two miles from the nearest major road, the I-15. The project is not considered a major transportation project. The project is only anticipated to generate approximately 359 daily vehicle trips.

Therefore, as the project is beyond 1,000 feet from a major transportation project and does not generate more than 50,000 vehicles per day, a project-specific health risk assessment is not required or warranted. Impacts to nearby sensitive receptors are considered to be less than significant.

6.2.3 Operations-Related Odor Impacts

Potential sources that may emit odors during the on-going operations of the proposed project would include odor emissions from vehicular emissions and trash storage areas. As the project is that of a

residential use, no significant impact related to odors would occur during the on-going operations of the proposed project.

6.3 Cumulative Regional Air Quality Impacts

Cumulative projects include local development as well as general growth within the project area. However, as with most development, the greatest source of emissions is from mobile sources, which travel well out of the local area. Therefore, from an air quality standpoint, the cumulative analysis would extend beyond any local projects and when wind patterns are considered, would cover an even larger area. Accordingly, the cumulative analysis for the project's air quality must be generic by nature.

The project area is out of attainment for both ozone and particulate matter. Construction and operation of cumulative projects will further degrade the air quality of the Mojave Desert Air Basin. The greatest cumulative impact on the quality of regional air cell will be the incremental addition of pollutants mainly from increased traffic from residential, commercial, and industrial development and the use of heavy equipment and trucks associated with the construction of these projects. Air quality will be temporarily degraded during construction activities that occur separately or simultaneously. However, in accordance with the MDAQMD methodology, projects that do not exceed the MDAQMD criteria or can be mitigated to less than criteria levels are not significant and do not add to the overall cumulative impact.

Project operations would generate emissions of NO_x, ROG, CO, SO₂, PM₁₀, and PM_{2.5}, which would not exceed the MDAQMD regional thresholds and would not be expected to result in ground level concentrations that exceed the NAAQS or CAAQS. Therefore, operation of the project would not result in a cumulatively considerable net increase for non-attainment of criteria pollutants or ozone precursors. As a result, the project would result in a less than significant cumulative impact for operational emissions.

6.4 Air Quality Compliance

The California Environmental Quality Act (CEQA) requires a discussion of any inconsistencies between a proposed project and applicable General Plans and Regional Plans (CEQA Guidelines Section 15125). According to the MDAQMD, a project is non-conforming if it conflicts with or delays implementation of any applicable attainment or maintenance plan.

A project is conforming if it complies with all applicable District rules and regulations, complies with all proposed control measures that are not yet adopted from the applicable plan(s), and is consistent with the growth forecasts in the applicable plan(s) (or is directly included in the applicable plan). Conformity with growth forecasts can be established by demonstrating that the project is consistent with the land use plan that was used to generate the growth forecast. An example of a non-conforming project would be one that increases the gross number of dwelling units, increases the number of trips, and/or increases the overall vehicle miles traveled in an affected area (relative to the applicable land use plan). The "one map approach" is employed by the County of San Bernardino, as it permits the use of a single map showing both General Plan land use designations and zoning classifications. The one-map approach assures that there will always be land use consistency between the County's General Plan and its Zoning Code.

The project site is located within the City of Victorville. The proposed project will be a single-family residential community. Per the City's General Plan Land Use & Zoning Districts map, the current land use zoning district is Low Density Residential (R-1). As shown by the results of this air analysis, the project's emissions do not exceed any MDAQMD thresholds during either short-term construction or long-term operation of the project. Therefore, as the project is a residential use, the proposed project is not anticipated to exceed the Attainment Plan assumptions for the project site.

Based on the above, the proposed project would not conflict with implementation of the MDAQMD Attainment Plans, impacts are considered to be less than significant.

7.0 Greenhouse Gas Impact Analysis

7.1 Construction Greenhouse Gas Emissions Impact

The greenhouse gas emissions from project construction equipment and worker vehicles are shown in Table 10. The emissions are from all phases of construction. The total construction emissions amortized over a period of 30 years are estimated at 26.95 metric tons of CO₂e per year. Annual CalEEMod output calculations are provided in Appendix A.

Table 10: Construction Greenhouse Gas Emissions

Year	Metric Tons Per Year					
	Bio-CO2	NBio-CO2	Total CO2	CH4	N2O	CO2e (MT)
2024	0.00	210.00	210.00	0.01	0.01	213.00
2025	0.00	491.00	491.00	0.01	0.02	496.00
2026	0.00	98.60	98.60	0.00	0.00	99.60
Total	0.00	799.60	799.60	0.02	0.03	808.60
Annualized Construction Emissions						26.95
Notes: 1. MTCO ₂ e=metric tons of carbon dioxide equivalents (includes carbon dioxide, methane and nitrous oxide). 2. The emissions are averaged over 30 years. * CalEEMod output (Appendix A)						

7.2 Operational Greenhouse Gas Emissions Impact

Operational emissions occur over the life of the project. Table 11 below shows that the subtotal for the proposed project would result in annual emissions of 3,147.91 MT CO₂e per. As shown in Table 11, the project’s total GHG emissions would not exceed the MDAQMD annual threshold of 100,000 MTCO₂e or the MDAQMD daily threshold of 548,000 pounds of CO₂e.

<Table 11, next page>

Table 11: Opening Year Project-Related Greenhouse Gas Emissions

Category	Greenhouse Gas Emissions (Metric Tons/Year) ¹						(lbs/day)
	Bio-CO ₂	NonBio-CO ₂	CO ₂	CH ₄	N ₂ O	CO ₂ e	CO ₂ e
Area Sources ²	0.00	1.71	1.71	0.00	0.00	1.81	21.00
Energy Usage ³	0.00	271.00	271.00	0.02	0.00	272.00	1,640.00
Mobile Sources ⁴	0.00	295.00	295.00	0.01	0.02	301.00	1,945.00
Solid Waste ⁵	37.20	0.00	37.20	3.72	0.00	130.00	787.00
Water ⁶	1.82	8.44	10.26	0.19	0.00	16.30	98.50
Total Operational Emissions	39.02	576.15	615.17	3.94	0.02	721.11	4,491.50
Construction ⁷	0.00	26.65	26.65	0.00	0.00	26.95	9,865.00
Combined Emissions	39.02	602.80	641.82	3.94	0.02	748.06	-
County of San Bernardino GHG Emissions Reduction Plan Threshold						3,000	-
MDAQMD GHG Thresholds						100,000	548,000
Exceeds Threshold?						No	No
Notes:							
¹ Source: CalEEMod Version 2022.1.1.29							
² Area sources consist of GHG emissions from consumer products, architectural coatings, and landscape equipment.							
³ Energy usage consist of GHG emissions from electricity and natural gas usage.							
⁴ Mobile sources consist of GHG emissions from vehicles.							
⁵ Solid waste includes the CO ₂ and CH ₄ emissions created from the solid waste placed in landfills.							
⁶ Water includes GHG emissions from electricity used for transport of water and processing of wastewater.							
⁷ Construction GHG emissions based on a 30 year amortization rate.							

7.3 Greenhouse Gas Plan Consistency

The proposed project would have the potential to conflict with any applicable plan, policy or regulation of an agency adopted for the purpose of reducing the emissions of greenhouse gases.

County of San Bernardino Emissions Reduction Plan

According to the *County of San Bernardino Greenhouse Gas Emissions Reduction Plan*, "all development projects, including those otherwise determined to be exempt from CEQA will be subject to applicable Development Code provisions, including the GHG performance standards, and state requirements, such as the California Building Code requirements for energy efficiency. With the application of the GHG performance standards, projects that are exempt from CEQA and small projects that do not exceed 3,000 MTCO₂e per year will be considered to be consistent with the Plan and determined to have a less than significant individual and cumulative impact for GHG emissions." The Reduction Plan also states that "the 3,000 MTCO₂e per year value was chosen as the medial value and is used in defining small projects that must include the Performance Standards as described in Attachment B (of the *County of San Bernardino Greenhouse Gas Emissions Reduction Plan*), but do not need to use the Screening Tables or alternative GHG mitigation analysis described in Attachment D (of the *County of San Bernardino Greenhouse Gas Emissions Reduction Plan*)."

The project's total net operational GHG emissions do not exceed the County's screening threshold of 3,000 MTCO₂e per year. Therefore, the project does not need to accrue points using the screening tables and is consistent with the GHG Plan, pursuant to Section 15183.5 of the State CEQA Guidelines. As mentioned above, the project is expected to comply with the performance standards for residential uses as detailed in the *County of San Bernardino Greenhouse Gas Emissions Reduction Plan* (see Appendix A for details on the performance standards for residential projects). The proposed project will not result in substantial emissions of greenhouse gases and will not conflict with the Green County initiatives.

7.4 Cumulative Greenhouse Gas Impacts

Although the project is expected to emit GHGs, the emission of GHGs by a single project into the atmosphere is not itself necessarily an adverse environmental effect. Rather, it is the increased accumulation of GHG from more than one project and many sources in the atmosphere that may result in global climate change. Therefore, in the case of global climate change, the proximity of the project to other GHG emission generating activities is not directly relevant to the determination of a cumulative impact because climate change is a global condition. According to CAPCOA, "GHG impacts are exclusively cumulative impacts; there are no non-cumulative GHG emission impacts from a climate change perspective."⁶ The resultant consequences of that climate change can cause adverse environmental effects. A project's GHG emissions typically would be very small in comparison to state or global GHG emissions and, consequently, they would, in isolation, have no significant direct impact on climate change.

The state has mandated a goal of reducing statewide emissions to 1990 levels by 2020, even though statewide population and commerce are predicted to continue to expand. In order to achieve this goal, CARB is in the process of establishing and implementing regulations to reduce statewide GHG emissions. The project was found to be below both the MDAQMD GHG thresholds and County of San Bernardino GHG Emissions Reduction Plan threshold. Therefore, consistent with CEQA Guidelines Section 15064h(3),⁷ the County, as lead agency, has determined that the project's contribution to cumulative GHG emissions and global climate change would be less than significant if the project is consistent with the applicable regulatory plans and policies to reduce GHG emissions.

6 Source: California Air Pollution Control Officers Association, CEQA & Climate change: Evaluating and Addressing Greenhouse Gas Emissions from Projects Subject to the California Environmental Quality Act, (2008).

7 The State CEQA Guidelines were amended in response to SB 97. In particular, the State CEQA Guidelines were amended to specify that compliance with a GHG emissions reduction program renders a cumulative impact insignificant. Per State CEQA Guidelines Section 15064(h)(3), a project's incremental contribution to a cumulative impact can be found not cumulatively considerable if the project will comply with an approved plan or mitigation program that provides specific requirements that will avoid or substantially lessen the cumulative problem within the geographic area of the project. To qualify, such a plan or program must be specified in law or adopted by the public agency with jurisdiction over the affected resources through a public review process to implement, interpret, or make specific the law enforced or administered by the public agency. Examples of such programs include a "water quality control plan, air quality attainment or maintenance plan, integrated waste management plan, habitat conservation plan, natural community conservation plan, [and] plans or regulations for the reduction of greenhouse gas emissions."

8.0 Energy Analysis

Information from the CalEEMod 2022.1.1.29 Daily and Annual Outputs contained in the air quality and greenhouse gas analyses above was utilized for this analysis. The CalEEMod outputs detail project related construction equipment, transportation energy demands, and facility energy demands.

8.1 Construction Energy Demand

8.1.1 Construction Equipment Electricity Usage Estimates

Electrical service will be provided by Southern California Edison (SCE). Based on the 2017 National Construction Estimator, Richard Pray (2017)⁸, the typical power cost per 1,000 square feet of building construction per month is estimated to be \$2.32. The project plans to develop the site 41,095 square feet of the new treatment campus over the course of approximately 19 months. Based on Table 12, the total power cost of the on-site electricity usage during the construction of the proposed project is estimated to be approximately \$1,811.47. As shown in Table 12, the total electricity usage from Project construction related activities is estimated to be approximately 32,936 kWh.⁹

Table 12: Project Construction Power Cost and Electricity Usage

Power Cost (per 1,000 square foot of building per month of construction)	Total Building Size (1,000 Square Foot) ¹	Construction Duration (months)	Total Project Construction Power Cost
\$2.32	41.095	19	\$1,811.47

Cost per kWh	Total Project Construction Electricity Usage (kWh)
\$0.06	32,936

* Assumes the project will be under the GS-1 General Service rate under SCE.

⁸ Pray, Richard. 2017 National Construction Estimator. Carlsbad: Craftsman Book Company, 2017.

⁹ LADWP's Small Commercial & Multi-Family Service (A-1) is approximately \$0.06 per kWh of electricity Southern California Edison (SCE). Rates & Pricing Choices: General Service/Industrial Rates. https://library.sce.com/content/dam/sce-doclib/public/regulatory/historical/electric/2020/schedules/general-service-&-industrial-rates/ELECTRIC_SCHEDULES_GS-1_2020.pdf

8.1.2 Construction Equipment Fuel Estimates

Using the CalEEMod data input, the project’s construction phase would consume electricity and fossil fuels as a single energy demand, that is, once construction is completed their use would cease. CARB’s 2017 Emissions Factors Tables show that on average aggregate fuel consumption (gasoline and diesel fuel) would be approximately 18.5 hp-hr-gal.¹⁰ As presented in Table 13 below, project construction activities would consume an estimated 46,164 gallons of diesel fuel.

Table 13: Construction Equipment Fuel Consumption Estimates

Phase	Number of Days	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor	HP hrs/day	Total Fuel Consumption (gal diesel fuel) ¹
Site Preparation	10	Rubber Tired Dozers	3	8	367	0.4	3,523	1,904
	10	Tractors/Loaders/Backhoes	4	8	84	0.37	995	538
Grading	30	Excavators	2	8	36	0.38	219	355
	30	Graders	1	8	148	0.41	485	787
	30	Rubber Tired Dozers	1	8	367	0.4	1,174	1,904
	30	Scrapers	2	8	423	0.48	3,249	5,268
	30	Tractors/Loaders/Backhoes	2	8	84	0.37	497	806
Building Construction	300	Cranes	1	7	367	0.29	745	12,081
	300	Forklifts	3	8	82	0.2	394	6,383
	300	Generator Sets	1	8	14	0.74	83	1,344
	300	Tractors/Loaders/Backhoes	3	7	84	0.37	653	10,584
	300	Welders	1	8	46	0.45	166	2,685
Paving	20	Pavers	2	8	81	0.42	544	588
	20	Paving Equipment	2	8	89	0.36	513	554
	20	Rollers	2	8	36	0.38	219	237
Architectural Coating	25	Air Compressors	1	6	37	0.48	107	144
CONSTRUCTION FUEL DEMAND (gallons of diesel fuel)								46,164

Notes:

¹Using Carl Moyer Guidelines Table D-21 Fuel consumption rate factors (bhp-hr/gal) for engines less than 750 hp.
 (Source: https://ww2.arb.ca.gov/sites/default/files/2020-06/2017_cmpgl.pdf)

8.1.3 Construction Worker Fuel Estimates

It is assumed that all construction worker trips are from light duty autos (LDA) along area roadways. With respect to estimated VMT, the construction worker trips would generate an estimated 580,761 VMT. Vehicle fuel efficiencies for construction workers were estimated in the air quality and greenhouse gas

¹⁰ Aggregate fuel consumption rate for all equipment was estimated at 18.5 hp-hr/day (from CARB’s 2017 Emissions Factors Tables and fuel consumption rate factors as shown in Table D-21 of the Moyer Guidelines: (https://ww2.arb.ca.gov/sites/default/files/2020-06/2017_cmpgl.pdf)).

analysis using information generated using CARB’s EMFAC model (see Appendix B for details). Table 14 shows that an estimated 18,764 gallons of fuel would be consumed for construction worker trips.

Table 14: Construction Worker Fuel Consumption Estimates

Phase	Number of Days	Worker Trips/Day	Trip Length (miles)	Vehicle Miles Traveled	Average Vehicle Fuel Economy (mpg)	Estimated Fuel Consumption (gallons)
Site Preparation	10	17.5	18.5	3237.5	30.95	105
Grading	30	20	18.5	11,100	30.95	359
Building Construction	300	99.4	18.5	551,670	30.95	17,825
Paving	20	15	18.5	5,550	30.95	179
Architectural Coating	25	19.9	18.5	9,204	30.95	297
Total Construction Worker Fuel Consumption						18,764

Notes:

¹Assumptions for the worker trip length and vehicle miles traveled are consistent with CalEEMod 2022.1.1.29 defaults.

8.1.4 Construction Vendor/Hauling Fuel Estimates

Tables 15 and 16 show the estimated fuel consumption for vendor and hauling during building construction and architectural coating. With respect to estimated VMT, the vendor and hauling trips would generate an estimated 70,308 VMT. For the architectural coatings it is assumed that the contractors would be responsible for bringing coatings and equipment with them in their light duty vehicles.¹¹ Tables 15 and 16 show that an estimated 8,735 gallons of fuel would be consumed for vendor and hauling trips.

Table 15: Construction Vendor Fuel Consumption Estimates (MHD Trucks)¹

Phase	Number of Days	Vendor Trips/Day	Trip Length (miles)	Vehicle Miles Traveled	Average Vehicle Fuel Economy (mpg)	Estimated Fuel Consumption (gallons)
Site Preparation	10	0	10.2	0	9.22	0
Grading	30	0	10.2	0	9.22	0
Building Construction	300	14.8	10.2	45,288	9.22	4,912
Paving	20	5	10.2	1,020	9.22	111
Architectural Coating	25	0	10.2	0	9.22	0
Total Vendor Fuel Consumption						5,023

Notes:

¹Assumptions for the vendor trip length and vehicle miles traveled are consistent with CalEEMod 2022.1.1.29 defaults.

¹¹ Vendors delivering construction material or hauling debris from the site during grading would use medium to heavy duty vehicles with an average fuel consumption of 9.22 mpg for medium heavy-duty trucks and 6.74 mpg for heavy heavy-duty trucks (see Appendix B for details).

Table 16: Construction Hauling Fuel Consumption Estimates (HHD Trucks)¹

Phase	Number of Days	Hauling Trips/Day	Trip Length (miles)	Vehicle Miles Traveled	Average Vehicle Fuel Economy (mpg)	Estimated Fuel Consumption (gallons)
Site Preparation	10	0	20	0	6.74	0
Grading	30	41.7	20	25,020	6.74	3,712
Building Construction	300	0	20	0	6.74	0
Paving	20	0	20	0	6.74	0
Architectural Coating	25	0	20	0	6.74	0
Total Construction Hauling Fuel Consumption						3,712

Notes:

¹Assumptions for the hauling trip length and vehicle miles traveled are consistent with CalEEMod 2022.1.1.29 defaults.

8.1.5 Construction Energy Efficiency/Conservation Measures

Construction equipment used over the approximately 19-month construction phase would conform to CARB regulations and California emissions standards and is evidence of related fuel efficiencies. In addition, the CARB Airborne Toxic Control Measure limits idling times of construction vehicles to no more than five minutes, thereby minimizing unnecessary and wasteful consumption of fuel due to unproductive idling of construction equipment. Furthermore, the project has been designed in compliance with California’s Energy Efficiency Standards and 2022 CALGreen Standards.

Construction of the proposed residential development would require the typical use of energy resources. There are no unusual project characteristics or construction processes that would require the use of equipment that would be more energy intensive than is used for comparable activities; or equipment that would not conform to current emissions standards (and related fuel efficiencies). Equipment employed in construction of the project would therefore not result in inefficient wasteful, or unnecessary consumption of fuel.

8.2 Operational Energy Demand

Energy consumption in support of or related to project operations would include transportation energy demands (energy consumed by employee and patron vehicles accessing the project site) and facilities energy demands (energy consumed by building operations and site maintenance activities).

8.2.1 Transportation Fuel Consumption

The largest source of operational energy use would be vehicle operation of customers. The site is located in a rural area. Using the CalEEMod output, the average trip length for all vehicles was assumed to be 6.26 miles. To show a worst-case analysis, as the proposed project is an office project, it was assumed that vehicles would operate 365 days per year. Table 17 shows the worst-case estimated annual fuel

consumption for all classes of vehicles from autos to heavy-heavy trucks.¹² Table 17 shows that an estimated 32,337 gallons of fuel would be consumed per year for the operation of the proposed project.

Table 17: Estimated Vehicle Operations Fuel Consumption

Vehicle Type	Vehicle Mix	Number of Vehicles ¹	Average Trip (miles) ²	Daily VMT	Average Fuel Economy (mpg)	Total Gallons per Day	Total Annual Fuel Consumption (gallons)
Light Auto	Automobile	201.2	6.26	1,259	30.98	40.65	14,836
Light Truck	Automobile	22.8	6.26	143	25.45	5.60	2,044
Light Truck	Automobile	68.5	6.26	429	25.58	16.76	6,116
Medium Truck	Automobile	47.7	6.26	299	20.46	14.61	5,332
Light Heavy Truck	2-Axle Truck	8.8	6.26	55	16.46	3.35	1,225
Light Heavy Truck 10,000 lbs +	2-Axle Truck	2.4	6.26	15	15.72	0.95	346
Medium Heavy Truck	3-Axle Truck	4.4	6.26	28	7.68	3.61	1,317
Heavy Heavy Truck	4-Axle Truck	3.2	6.26	20	6.53	3.07	1,121
Total		359	--	2,247	--	88.59	--
Total Annual Fuel Consumption							32,337

Notes:

¹ Per the trip generation assessment, the project is to generate 359 total net new trips after reduction of existing uses. Default CalEEMod vehicle fleet mix utilized.

² Based on the size of the site and relative location, trips were assumed to be local rather than regional.

Trip generation generated by the proposed project are consistent with other similar residential uses of similar scale and configuration as reflected in the traffic assessment for the project. That is, the proposed project does not propose uses or operations that would inherently result in excessive and wasteful vehicle trips, nor associated excess and wasteful vehicle energy consumption. Therefore, project transportation energy consumption would not be considered inefficient, wasteful, or otherwise unnecessary.

8.2.2 Facility Energy Demands (Electricity and Natural Gas)

The annual natural gas and electricity demands were provided per the CalEEMod output and are provided in Table 18.

<Table 18, next page>

¹² Average fuel economy based on aggregate mileage calculated in EMFAC 2021 for 2027. See Appendix B for EMFAC output.

Table 18: Project Unmitigated Annual Operational Energy Demand Summary¹

Natural Gas Demand		kBTU/year
Congregate Care (Assisted Living)		1,523,131
Total		1,523,131
Electricity Demand		kWh/year
Congregate Care (Assisted Living)		595,630
Parking Lot		190,793
Total		786,423

Notes:

¹Taken from the CalEEMod 2022.1.1.29 annual output.

As shown in Table 18, the estimated electricity demand for the proposed project is approximately 786,423 kWh per year. In 2022, the residential sector of the County of San Bernardino consumed approximately 6,302 million kWh of electricity.¹³ In addition, the estimated natural gas consumption for the proposed project is approximately 1,523,131 kBTU per year. In 2022, the residential sector of the County of San Bernardino consumed approximately 267 million therms of gas.¹⁴ Therefore, the increase in both electricity and natural gas demand from the proposed project is insignificant compared to the County’s 2022 demand.

8.3 Renewable Energy and Energy Efficiency Plan Consistency

Regarding federal transportation regulations, the project site is located in an already developed area. Access to/from the project site is from existing roads. These roads are already in place so the project would not interfere with, nor otherwise obstruct intermodal transportation plans or projects that may be proposed pursuant to the ISTEA because SCAG is not planning for intermodal facilities in the project area.

Regarding the State’s Energy Plan and compliance with Title 24 CCR energy efficiency standards, the applicant is required to comply with the California Green Building Standard Code requirements for energy efficient buildings and appliances as well as utility energy efficiency programs implemented by the SCE and Southern California Gas Company.

Regarding the State’s Renewable Energy Portfolio Standards, the project would be required to meet or exceed the energy standards established in the California Green Building Standards Code, Title 24, Part 11 (CALGreen). CalGreen Standards require that new buildings reduce water consumption, employ building commissioning to increase building system efficiencies, divert construction waste from landfills, and install low pollutant-emitting finish materials.

¹³ California Energy Commission, Electricity Consumption by County. <https://ecdms.energy.ca.gov/elecbycounty.aspx>

¹⁴ California Energy Commission, Gas Consumption by County. <http://ecdms.energy.ca.gov/gasbycounty.aspx>

9.0 References

The following references were used in the preparing this analysis.

California Air Pollution Control Officers Association

2009 Health Risk Assessments for Proposed Land Use Projects

California Air Resources Board

2008 Resolution 08-43

2008 Recommended Approaches for Setting Interim Significance Thresholds for Greenhouse Gases under the California Environmental Quality Act

2008 ARB Recommended Interim Risk Management Policy for Inhalation-Based Residential Cancer Risk – Frequently Asked Questions

2008 Climate Change Scoping Plan, a framework for change.

2011 Supplement to the AB 32 Scoping Plan Functional Equivalent Document

2013 Revised Emission Factors for Gasoline Marketing Operations at California Gasoline Dispensing Facilities

2014 First Update to the Climate Change Scoping Plan, Building on the Framework Pursuant to AB32, the California Global Warming Solutions Act of 2006. May.

2017 California's 2017 Climate Change Scoping Plan. November.

2020 Historical Air Quality, Top 4 Summary

Governor's Office of Planning and Research

2008 CEQA and Climate: Addressing Climate Change Through California Environmental Quality Act (CEQA) Review

2009 CEQA Guideline Sections to be Added or Amended

Mojave Desert Air Quality Management District (MDAQMD)

2016 California Environmental Quality Act (CEQA) And Federal Conformity Guidelines. August

Office of Environmental Health Hazard Assessment

2015 Air Toxics Hot Spots Program Risk Assessment Guidelines

Appendix A:

CalEEMod Emissions Output

Behavioral Health Detailed Report

Table of Contents

1. Basic Project Information
 - 1.1. Basic Project Information
 - 1.2. Land Use Types
 - 1.3. User-Selected Emission Reduction Measures by Emissions Sector
2. Emissions Summary
 - 2.1. Construction Emissions Compared Against Thresholds
 - 2.2. Construction Emissions by Year, Unmitigated
 - 2.4. Operations Emissions Compared Against Thresholds
 - 2.5. Operations Emissions by Sector, Unmitigated
3. Construction Emissions Details
 - 3.1. Site Preparation (2025) - Unmitigated
 - 3.3. Grading (2025) - Unmitigated
 - 3.5. Building Construction (2025) - Unmitigated
 - 3.7. Building Construction (2026) - Unmitigated
 - 3.9. Building Construction (2027) - Unmitigated

3.11. Paving (2027) - Unmitigated

3.13. Architectural Coating (2027) - Unmitigated

4. Operations Emissions Details

4.1. Mobile Emissions by Land Use

4.1.1. Unmitigated

4.2. Energy

4.2.1. Electricity Emissions By Land Use - Unmitigated

4.2.3. Natural Gas Emissions By Land Use - Unmitigated

4.3. Area Emissions by Source

4.3.1. Unmitigated

4.4. Water Emissions by Land Use

4.4.1. Unmitigated

4.5. Waste Emissions by Land Use

4.5.1. Unmitigated

4.6. Refrigerant Emissions by Land Use

4.6.1. Unmitigated

4.7. Offroad Emissions By Equipment Type

4.7.1. Unmitigated

4.8. Stationary Emissions By Equipment Type

4.8.1. Unmitigated

4.9. User Defined Emissions By Equipment Type

4.9.1. Unmitigated

4.10. Soil Carbon Accumulation By Vegetation Type

4.10.1. Soil Carbon Accumulation By Vegetation Type - Unmitigated

4.10.2. Above and Belowground Carbon Accumulation by Land Use Type - Unmitigated

4.10.3. Avoided and Sequestered Emissions by Species - Unmitigated

5. Activity Data

5.1. Construction Schedule

5.2. Off-Road Equipment

5.2.1. Unmitigated

5.3. Construction Vehicles

5.3.1. Unmitigated

5.4. Vehicles

5.4.1. Construction Vehicle Control Strategies

5.5. Architectural Coatings

5.6. Dust Mitigation

5.6.1. Construction Earthmoving Activities

5.6.2. Construction Earthmoving Control Strategies

5.7. Construction Paving

5.8. Construction Electricity Consumption and Emissions Factors

5.9. Operational Mobile Sources

5.9.1. Unmitigated

5.10. Operational Area Sources

5.10.1. Hearths

5.10.1.1. Unmitigated

5.10.2. Architectural Coatings

5.10.3. Landscape Equipment

5.11. Operational Energy Consumption

5.11.1. Unmitigated

5.12. Operational Water and Wastewater Consumption

5.12.1. Unmitigated

5.13. Operational Waste Generation

5.13.1. Unmitigated

5.14. Operational Refrigeration and Air Conditioning Equipment

5.14.1. Unmitigated

5.15. Operational Off-Road Equipment

5.15.1. Unmitigated

5.16. Stationary Sources

5.16.1. Emergency Generators and Fire Pumps

5.16.2. Process Boilers

5.17. User Defined

5.18. Vegetation

5.18.1. Land Use Change

5.18.1.1. Unmitigated

5.18.1. Biomass Cover Type

5.18.1.1. Unmitigated

5.18.2. Sequestration

5.18.2.1. Unmitigated

6. Climate Risk Detailed Report

6.1. Climate Risk Summary

6.2. Initial Climate Risk Scores

6.3. Adjusted Climate Risk Scores

6.4. Climate Risk Reduction Measures

7. Health and Equity Details

7.1. CalEnviroScreen 4.0 Scores

7.2. Healthy Places Index Scores

7.3. Overall Health & Equity Scores

7.4. Health & Equity Measures

7.5. Evaluation Scorecard

7.6. Health & Equity Custom Measures

8. User Changes to Default Data

1. Basic Project Information

1.1. Basic Project Information

Data Field	Value
Project Name	Behavioral Health
Construction Start Date	8/28/2025
Operational Year	2027
Lead Agency	—
Land Use Scale	Project/site
Analysis Level for Defaults	County
Windspeed (m/s)	2.80
Precipitation (days)	1.40
Location	13333 Palmdale Rd, Victorville, CA 92392, USA
County	San Bernardino-Mojave Desert
City	Victorville
Air District	Mojave Desert AQMD
Air Basin	Mojave Desert
TAZ	6839
EDFZ	10
Electric Utility	Southern California Edison
Gas Utility	Southwest Gas Corp.
App Version	2022.1.1.29

1.2. Land Use Types

Land Use Subtype	Size	Unit	Lot Acreage	Building Area (sq ft)	Landscape Area (sq ft)	Special Landscape Area (sq ft)	Population	Description
Congregate Care (Assisted Living)	138	Dwelling Unit	8.63	41,095	0.00	—	457	—

Parking Lot	261	Space	5.00	0.00	20,000	—	—	—
-------------	-----	-------	------	------	--------	---	---	---

1.3. User-Selected Emission Reduction Measures by Emissions Sector

No measures selected

2. Emissions Summary

2.1. Construction Emissions Compared Against Thresholds

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Un/Mit.	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	12.9	31.7	31.6	0.05	1.37	7.89	9.26	1.26	3.99	5.25	—	5,551	5,551	0.23	0.13	5.97	5,573
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	12.9	33.1	31.2	0.08	1.37	7.89	9.26	1.26	3.99	5.25	—	9,703	9,703	0.28	0.52	0.19	9,865
Average Daily (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	1.13	7.76	13.5	0.02	0.28	1.02	1.29	0.25	0.27	0.50	—	2,967	2,967	0.09	0.09	1.84	2,999
Annual (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.21	1.42	2.47	< 0.005	0.05	0.19	0.24	0.05	0.05	0.09	—	491	491	0.01	0.02	0.30	496

2.2. Construction Emissions by Year, Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Year	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily - Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

2025	3.41	31.7	31.6	0.05	1.37	7.89	9.26	1.26	3.99	5.25	—	5,551	5,551	0.23	0.05	0.93	5,573
2026	1.56	10.8	20.8	0.03	0.39	1.42	1.81	0.35	0.34	0.69	—	4,279	4,279	0.16	0.13	5.97	4,328
2027	12.9	0.91	2.54	< 0.005	0.02	0.26	0.28	0.02	0.06	0.08	—	413	413	0.01	0.01	0.87	417
Daily - Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2025	3.39	33.1	31.2	0.08	1.37	7.89	9.26	1.26	3.99	5.25	—	9,703	9,703	0.28	0.52	0.19	9,865
2026	1.51	10.8	18.3	0.03	0.39	1.42	1.81	0.35	0.34	0.69	—	4,116	4,116	0.12	0.13	0.15	4,159
2027	12.9	10.3	17.9	0.03	0.34	1.42	1.77	0.32	0.34	0.66	—	4,085	4,085	0.12	0.13	0.14	4,126
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2025	0.49	4.47	4.83	0.01	0.18	0.70	0.88	0.16	0.27	0.44	—	1,269	1,269	0.04	0.05	0.48	1,287
2026	1.08	7.76	13.5	0.02	0.28	1.02	1.29	0.25	0.24	0.50	—	2,967	2,967	0.09	0.09	1.84	2,999
2027	1.13	1.64	2.87	< 0.005	0.06	0.19	0.25	0.05	0.05	0.10	—	596	596	0.02	0.02	0.31	601
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2025	0.09	0.82	0.88	< 0.005	0.03	0.13	0.16	0.03	0.05	0.08	—	210	210	0.01	0.01	0.08	213
2026	0.20	1.42	2.47	< 0.005	0.05	0.19	0.24	0.05	0.04	0.09	—	491	491	0.01	0.02	0.30	496
2027	0.21	0.30	0.52	< 0.005	0.01	0.04	0.05	0.01	0.01	0.02	—	98.6	98.6	< 0.005	< 0.005	0.05	99.6

2.4. Operations Emissions Compared Against Thresholds

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Un/Mit.	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	3.21	1.43	16.7	0.02	0.05	1.59	1.64	0.05	0.40	0.45	236	3,616	3,852	23.8	0.13	6.39	4,491
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	2.33	1.43	7.25	0.02	0.05	1.59	1.63	0.05	0.40	0.45	236	3,431	3,667	23.8	0.13	0.67	4,302

Average Daily (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	2.68	1.49	11.7	0.02	0.05	1.58	1.63	0.05	0.40	0.45	236	3,479	3,715	23.8	0.13	3.06	4,352
Annual (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Unmit.	0.49	0.27	2.13	< 0.005	0.01	0.29	0.30	0.01	0.07	0.08	39.1	576	615	3.94	0.02	0.51	721

2.5. Operations Emissions by Sector, Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Sector	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	1.52	0.97	8.67	0.02	0.01	1.59	1.60	0.01	0.40	0.42	—	1,910	1,910	0.08	0.09	5.87	1,945
Area	1.67	0.07	7.83	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	20.9	20.9	< 0.005	< 0.005	—	21.0
Energy	0.02	0.38	0.16	< 0.005	0.03	—	0.03	0.03	—	0.03	—	1,634	1,634	0.11	0.01	—	1,640
Water	—	—	—	—	—	—	—	—	—	—	11.0	51.0	62.0	1.13	0.03	—	98.5
Waste	—	—	—	—	—	—	—	—	—	—	225	0.00	225	22.5	0.00	—	787
Refrig.	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.52	0.52
Total	3.21	1.43	16.7	0.02	0.05	1.59	1.64	0.05	0.40	0.45	236	3,616	3,852	23.8	0.13	6.39	4,491
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	1.33	1.05	7.08	0.02	0.01	1.59	1.60	0.01	0.40	0.42	—	1,746	1,746	0.09	0.09	0.15	1,776
Area	0.98	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Energy	0.02	0.38	0.16	< 0.005	0.03	—	0.03	0.03	—	0.03	—	1,634	1,634	0.11	0.01	—	1,640
Water	—	—	—	—	—	—	—	—	—	—	11.0	51.0	62.0	1.13	0.03	—	98.5
Waste	—	—	—	—	—	—	—	—	—	—	225	0.00	225	22.5	0.00	—	787
Refrig.	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.52	0.52
Total	2.33	1.43	7.25	0.02	0.05	1.59	1.63	0.05	0.40	0.45	236	3,431	3,667	23.8	0.13	0.67	4,302

Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	1.34	1.07	7.63	0.02	0.01	1.58	1.60	0.01	0.40	0.42	—	1,783	1,783	0.09	0.09	2.54	1,816
Area	1.32	0.04	3.86	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	10.3	10.3	< 0.005	< 0.005	—	10.4
Energy	0.02	0.38	0.16	< 0.005	0.03	—	0.03	0.03	—	0.03	—	1,634	1,634	0.11	0.01	—	1,640
Water	—	—	—	—	—	—	—	—	—	—	11.0	51.0	62.0	1.13	0.03	—	98.5
Waste	—	—	—	—	—	—	—	—	—	—	225	0.00	225	22.5	0.00	—	787
Refrig.	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.52	0.52
Total	2.68	1.49	11.7	0.02	0.05	1.58	1.63	0.05	0.40	0.45	236	3,479	3,715	23.8	0.13	3.06	4,352
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Mobile	0.24	0.19	1.39	< 0.005	< 0.005	0.29	0.29	< 0.005	0.07	0.08	—	295	295	0.01	0.02	0.42	301
Area	0.24	0.01	0.71	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	1.71	1.71	< 0.005	< 0.005	—	1.72
Energy	< 0.005	0.07	0.03	< 0.005	0.01	—	0.01	0.01	—	0.01	—	271	271	0.02	< 0.005	—	272
Water	—	—	—	—	—	—	—	—	—	—	1.82	8.44	10.3	0.19	< 0.005	—	16.3
Waste	—	—	—	—	—	—	—	—	—	—	37.2	0.00	37.2	3.72	0.00	—	130
Refrig.	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.09	0.09
Total	0.49	0.27	2.13	< 0.005	0.01	0.29	0.30	0.01	0.07	0.08	39.1	576	615	3.94	0.02	0.51	721

3. Construction Emissions Details

3.1. Site Preparation (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	3.31	31.6	30.2	0.05	1.37	—	1.37	1.26	—	1.26	—	5,295	5,295	0.21	0.04	—	5,314

Dust From Material Movement	—	—	—	—	—	7.67	7.67	—	3.94	3.94	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	3.31	31.6	30.2	0.05	1.37	—	1.37	1.26	—	1.26	—	5,295	5,295	0.21	0.04	—	5,314
Dust From Material Movement	—	—	—	—	—	7.67	7.67	—	3.94	3.94	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.09	0.87	0.83	< 0.005	0.04	—	0.04	0.03	—	0.03	—	145	145	0.01	< 0.005	—	146
Dust From Material Movement	—	—	—	—	—	0.21	0.21	—	0.11	0.11	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.02	0.16	0.15	< 0.005	0.01	—	0.01	0.01	—	0.01	—	24.0	24.0	< 0.005	< 0.005	—	24.1
Dust From Material Movement	—	—	—	—	—	0.04	0.04	—	0.02	0.02	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.10	0.08	1.45	0.00	0.00	0.23	0.23	0.00	0.05	0.05	—	255	255	0.01	0.01	0.93	259
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.08	0.09	0.98	0.00	0.00	0.23	0.23	0.00	0.05	0.05	—	226	226	0.01	0.01	0.02	229
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	0.03	0.00	0.00	0.01	0.01	0.00	< 0.005	< 0.005	—	6.37	6.37	< 0.005	< 0.005	0.01	6.46
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	0.01	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	1.06	1.06	< 0.005	< 0.005	< 0.005	1.07
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

3.3. Grading (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	3.20	29.7	28.3	0.06	1.23	—	1.23	1.14	—	1.14	—	6,599	6,599	0.27	0.05	—	6,622
Dust From Material Movement	—	—	—	—	—	3.60	3.60	—	1.43	1.43	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.26	2.44	2.33	0.01	0.10	—	0.10	0.09	—	0.09	—	542	542	0.02	< 0.005	—	544
Dust From Material Movement	—	—	—	—	—	0.30	0.30	—	0.12	0.12	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.05	0.45	0.42	< 0.005	0.02	—	0.02	0.02	—	0.02	—	89.8	89.8	< 0.005	< 0.005	—	90.1
Dust From Material Movement	—	—	—	—	—	0.05	0.05	—	0.02	0.02	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Worker	0.09	0.11	1.11	0.00	0.00	0.26	0.26	0.00	0.06	0.06	—	258	258	0.01	0.01	0.03	262
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.06	3.36	0.72	0.02	0.06	0.75	0.81	0.06	0.19	0.25	—	2,846	2,846	< 0.005	0.46	0.16	2,982
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.01	0.01	0.10	0.00	0.00	0.02	0.02	0.00	0.01	0.01	—	21.9	21.9	< 0.005	< 0.005	0.04	22.2
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	0.28	0.06	< 0.005	< 0.005	0.06	0.07	< 0.005	0.02	0.02	—	234	234	< 0.005	0.04	0.22	245
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	0.02	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	3.62	3.62	< 0.005	< 0.005	0.01	3.67
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	< 0.005	0.05	0.01	< 0.005	< 0.005	0.01	0.01	< 0.005	< 0.005	< 0.005	—	38.7	38.7	< 0.005	0.01	0.04	40.6

3.5. Building Construction (2025) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	1.13	10.4	13.0	0.02	0.43	—	0.43	0.40	—	0.40	—	2,398	2,398	0.10	0.02	—	2,406
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.09	0.80	1.00	< 0.005	0.03	—	0.03	0.03	—	0.03	—	183	183	0.01	< 0.005	—	184

Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.02	0.15	0.18	< 0.005	0.01	—	0.01	0.01	—	0.01	—	30.3	30.3	< 0.005	< 0.005	—	30.4
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.44	0.53	5.54	0.00	0.00	1.30	1.30	0.00	0.30	0.30	—	1,283	1,283	0.06	0.05	0.14	1,299
Vendor	0.02	0.50	0.21	< 0.005	0.01	0.13	0.13	0.01	0.03	0.04	—	470	470	< 0.005	0.06	0.03	489
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.03	0.04	0.47	0.00	0.00	0.10	0.10	0.00	0.02	0.02	—	101	101	< 0.005	< 0.005	0.17	102
Vendor	< 0.005	0.04	0.02	< 0.005	< 0.005	0.01	0.01	< 0.005	< 0.005	< 0.005	—	35.9	35.9	< 0.005	< 0.005	0.04	37.4
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.01	0.01	0.09	0.00	0.00	0.02	0.02	0.00	< 0.005	< 0.005	—	16.7	16.7	< 0.005	< 0.005	0.03	16.9
Vendor	< 0.005	0.01	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	5.94	5.94	< 0.005	< 0.005	0.01	6.18
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

3.7. Building Construction (2026) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	1.07	9.85	13.0	0.02	0.38	—	0.38	0.35	—	0.35	—	2,397	2,397	0.10	0.02	—	2,405
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	1.07	9.85	13.0	0.02	0.38	—	0.38	0.35	—	0.35	—	2,397	2,397	0.10	0.02	—	2,405
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.77	7.04	9.26	0.02	0.27	—	0.27	0.25	—	0.25	—	1,712	1,712	0.07	0.01	—	1,718
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.14	1.28	1.69	< 0.005	0.05	—	0.05	0.05	—	0.05	—	283	283	0.01	< 0.005	—	284
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.48	0.44	7.67	0.00	0.00	1.30	1.30	0.00	0.30	0.30	—	1,421	1,421	0.06	0.05	4.81	1,442
Vendor	0.02	0.46	0.19	< 0.005	0.01	0.13	0.13	0.01	0.03	0.04	—	461	461	< 0.005	0.06	1.16	481
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Worker	0.42	0.48	5.11	0.00	0.00	1.30	1.30	0.00	0.30	0.30	—	1,258	1,258	0.02	0.05	0.12	1,273
Vendor	0.02	0.49	0.20	< 0.005	0.01	0.13	0.13	0.01	0.03	0.04	—	461	461	< 0.005	0.06	0.03	480
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.31	0.37	4.11	0.00	0.00	0.93	0.93	0.00	0.22	0.22	—	925	925	0.02	0.04	1.48	937
Vendor	0.01	0.35	0.14	< 0.005	< 0.005	0.09	0.09	< 0.005	0.02	0.03	—	329	329	< 0.005	0.04	0.36	343
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.06	0.07	0.75	0.00	0.00	0.17	0.17	0.00	0.04	0.04	—	153	153	< 0.005	0.01	0.25	155
Vendor	< 0.005	0.06	0.03	< 0.005	< 0.005	0.02	0.02	< 0.005	< 0.005	0.01	—	54.5	54.5	< 0.005	0.01	0.06	56.8
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

3.9. Building Construction (2027) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	1.03	9.39	12.9	0.02	0.34	—	0.34	0.31	—	0.31	—	2,397	2,397	0.10	0.02	—	2,405
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.12	1.08	1.49	< 0.005	0.04	—	0.04	0.04	—	0.04	—	277	277	0.01	< 0.005	—	278

Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.02	0.20	0.27	< 0.005	0.01	—	0.01	0.01	—	0.01	—	45.8	45.8	< 0.005	< 0.005	—	46.0
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.41	0.44	4.76	0.00	0.00	1.30	1.30	0.00	0.30	0.30	—	1,237	1,237	0.02	0.05	0.11	1,252
Vendor	0.01	0.47	0.19	< 0.005	0.01	0.13	0.13	0.01	0.03	0.04	—	451	451	< 0.005	0.06	0.03	469
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.05	0.06	0.61	0.00	0.00	0.15	0.15	0.00	0.04	0.04	—	147	147	< 0.005	0.01	0.22	149
Vendor	< 0.005	0.05	0.02	< 0.005	< 0.005	0.01	0.02	< 0.005	< 0.005	< 0.005	—	52.1	52.1	< 0.005	0.01	0.05	54.2
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.01	0.01	0.11	0.00	0.00	0.03	0.03	0.00	0.01	0.01	—	24.3	24.3	< 0.005	< 0.005	0.04	24.7
Vendor	< 0.005	0.01	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	< 0.005	—	8.62	8.62	< 0.005	< 0.005	0.01	8.97
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

3.11. Paving (2027) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.74	6.94	9.95	0.01	0.30	—	0.30	0.27	—	0.27	—	1,511	1,511	0.06	0.01	—	1,516
Paving	0.66	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.04	0.38	0.55	< 0.005	0.02	—	0.02	0.02	—	0.02	—	82.8	82.8	< 0.005	< 0.005	—	83.1
Paving	0.04	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.01	0.07	0.10	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	13.7	13.7	< 0.005	< 0.005	—	13.8
Paving	0.01	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.06	0.07	0.72	0.00	0.00	0.20	0.20	0.00	0.05	0.05	—	187	187	< 0.005	0.01	0.02	189
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	0.04	0.00	0.00	0.01	0.01	0.00	< 0.005	< 0.005	—	10.5	10.5	< 0.005	< 0.005	0.02	10.7
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	0.01	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	1.74	1.74	< 0.005	< 0.005	< 0.005	1.77
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

3.13. Architectural Coating (2027) - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Location	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Onsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.11	0.83	1.13	< 0.005	0.02	—	0.02	0.02	—	0.02	—	134	134	0.01	< 0.005	—	134
Architectural Coatings	12.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.11	0.83	1.13	< 0.005	0.02	—	0.02	0.02	—	0.02	—	134	134	0.01	< 0.005	—	134
Architectural Coatings	12.7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	0.01	0.06	0.08	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	9.14	9.14	< 0.005	< 0.005	—	9.18
Architectural Coatings	0.87	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Off-Road Equipment	< 0.005	0.01	0.01	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	1.51	1.51	< 0.005	< 0.005	—	1.52
Architectural Coatings	0.16	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Onsite truck	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Offsite	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.09	0.08	1.42	0.00	0.00	0.26	0.26	0.00	0.06	0.06	—	279	279	< 0.005	0.01	0.87	283
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	0.08	0.09	0.95	0.00	0.00	0.26	0.26	0.00	0.06	0.06	—	247	247	< 0.005	0.01	0.02	250
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Average Daily	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Worker	0.01	0.01	0.07	0.00	0.00	0.02	0.02	0.00	< 0.005	< 0.005	—	17.4	17.4	< 0.005	< 0.005	0.03	17.7
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Worker	< 0.005	< 0.005	0.01	0.00	0.00	< 0.005	< 0.005	0.00	< 0.005	< 0.005	—	2.89	2.89	< 0.005	< 0.005	< 0.005	2.93
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	0.00	0.00	0.00	0.00

4. Operations Emissions Details

4.1. Mobile Emissions by Land Use

4.1.1. Unmitigated

Mobile source emissions results are presented in Sections 2.6. No further detailed breakdown of emissions is available.

4.2. Energy

4.2.1. Electricity Emissions By Land Use - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	—	868	868	0.05	0.01	—	871
Parking Lot	—	—	—	—	—	—	—	—	—	—	—	278	278	0.02	< 0.005	—	279
Total	—	—	—	—	—	—	—	—	—	—	—	1,146	1,146	0.07	0.01	—	1,151

Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	—	868	868	0.05	0.01	—	871
Parking Lot	—	—	—	—	—	—	—	—	—	—	—	278	278	0.02	< 0.005	—	279
Total	—	—	—	—	—	—	—	—	—	—	—	1,146	1,146	0.07	0.01	—	1,151
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	—	144	144	0.01	< 0.005	—	144
Parking Lot	—	—	—	—	—	—	—	—	—	—	—	46.0	46.0	< 0.005	< 0.005	—	46.2
Total	—	—	—	—	—	—	—	—	—	—	—	190	190	0.01	< 0.005	—	190

4.2.3. Natural Gas Emissions By Land Use - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	0.02	0.38	0.16	< 0.005	0.03	—	0.03	0.03	—	0.03	—	488	488	0.04	< 0.005	—	489
Parking Lot	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Total	0.02	0.38	0.16	< 0.005	0.03	—	0.03	0.03	—	0.03	—	488	488	0.04	< 0.005	—	489

Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	0.02	0.38	0.16	< 0.005	0.03	—	0.03	0.03	—	0.03	—	488	488	0.04	< 0.005	—	489
Parking Lot	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Total	0.02	0.38	0.16	< 0.005	0.03	—	0.03	0.03	—	0.03	—	488	488	0.04	< 0.005	—	489
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	< 0.005	0.07	0.03	< 0.005	0.01	—	0.01	0.01	—	0.01	—	80.8	80.8	0.01	< 0.005	—	81.0
Parking Lot	0.00	0.00	0.00	0.00	0.00	—	0.00	0.00	—	0.00	—	0.00	0.00	0.00	0.00	—	0.00
Total	< 0.005	0.07	0.03	< 0.005	0.01	—	0.01	0.01	—	0.01	—	80.8	80.8	0.01	< 0.005	—	81.0

4.3. Area Emissions by Source

4.3.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Source	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Consumer Products	0.90	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Architectural Coatings	0.09	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Landscape Equipment	0.69	0.07	7.83	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	20.9	20.9	< 0.005	< 0.005	—	21.0
Total	1.67	0.07	7.83	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	20.9	20.9	< 0.005	< 0.005	—	21.0
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Consumer Products	0.90	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Architectural Coatings	0.09	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	0.98	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Consumer Products	0.16	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Architectural Coatings	0.02	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Landscape Equipment	0.06	0.01	0.71	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	1.71	1.71	< 0.005	< 0.005	—	1.72
Total	0.24	0.01	0.71	< 0.005	< 0.005	—	< 0.005	< 0.005	—	< 0.005	—	1.71	1.71	< 0.005	< 0.005	—	1.72

4.4. Water Emissions by Land Use

4.4.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Congreg Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	11.0	48.3	59.3	1.13	0.03	—	95.7
Parking Lot	—	—	—	—	—	—	—	—	—	—	0.00	2.74	2.74	< 0.005	< 0.005	—	2.75
Total	—	—	—	—	—	—	—	—	—	—	11.0	51.0	62.0	1.13	0.03	—	98.5
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congreg ate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	11.0	48.3	59.3	1.13	0.03	—	95.7
Parking Lot	—	—	—	—	—	—	—	—	—	—	0.00	2.74	2.74	< 0.005	< 0.005	—	2.75
Total	—	—	—	—	—	—	—	—	—	—	11.0	51.0	62.0	1.13	0.03	—	98.5
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congreg ate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	1.82	7.99	9.82	0.19	< 0.005	—	15.8
Parking Lot	—	—	—	—	—	—	—	—	—	—	0.00	0.45	0.45	< 0.005	< 0.005	—	0.45
Total	—	—	—	—	—	—	—	—	—	—	1.82	8.44	10.3	0.19	< 0.005	—	16.3

4.5. Waste Emissions by Land Use

4.5.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
----------	-----	-----	----	-----	-------	-------	-------	--------	--------	--------	------	-------	------	-----	-----	---	------

Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	225	0.00	225	22.5	0.00	—	787
Parking Lot	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	225	0.00	225	22.5	0.00	—	787
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	225	0.00	225	22.5	0.00	—	787
Parking Lot	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	225	0.00	225	22.5	0.00	—	787
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	37.2	0.00	37.2	3.72	0.00	—	130
Parking Lot	—	—	—	—	—	—	—	—	—	—	0.00	0.00	0.00	0.00	0.00	—	0.00
Total	—	—	—	—	—	—	—	—	—	—	37.2	0.00	37.2	3.72	0.00	—	130

4.6. Refrigerant Emissions by Land Use

4.6.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.52	0.52
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.52	0.52
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.52	0.52
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.52	0.52
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Congregate Care (Assisted Living)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.09	0.09
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	0.09	0.09

4.7. Offroad Emissions By Equipment Type

4.7.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Equipment Type	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
----------------	-----	-----	----	-----	-------	-------	-------	--------	--------	--------	------	-------	------	-----	-----	---	------

Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.8. Stationary Emissions By Equipment Type

4.8.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Equipment Type	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.9. User Defined Emissions By Equipment Type

4.9.1. Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Equipment Type	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.10. Soil Carbon Accumulation By Vegetation Type

4.10.1. Soil Carbon Accumulation By Vegetation Type - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Vegetation	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.10.2. Above and Belowground Carbon Accumulation by Land Use Type - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Land Use	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Total	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

4.10.3. Avoided and Sequestered Emissions by Species - Unmitigated

Criteria Pollutants (lb/day for daily, ton/yr for annual) and GHGs (lb/day for daily, MT/yr for annual)

Species	ROG	NOx	CO	SO2	PM10E	PM10D	PM10T	PM2.5E	PM2.5D	PM2.5T	BCO2	NBCO2	CO2T	CH4	N2O	R	CO2e
Daily, Summer (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Avoided	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Sequestered	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Removed	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Daily, Winter (Max)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Avoided	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Sequestered	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Removed	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Annual	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Avoided	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Sequestered	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Removed	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Subtotal	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

5. Activity Data

5.1. Construction Schedule

Phase Name	Phase Type	Start Date	End Date	Days Per Week	Work Days per Phase	Phase Description
Site Preparation	Site Preparation	9/26/2025	10/10/2025	5.00	10.0	—
Grading	Grading	10/11/2025	11/22/2025	5.00	30.0	—
Building Construction	Building Construction	11/23/2025	2/28/2027	5.00	330	—

Paving	Paving	3/1/2027	3/26/2027	5.00	20.0	—
Architectural Coating	Architectural Coating	3/29/2027	4/30/2027	5.00	25.0	—

5.2. Off-Road Equipment

5.2.1. Unmitigated

Phase Name	Equipment Type	Fuel Type	Engine Tier	Number per Day	Hours Per Day	Horsepower	Load Factor
Site Preparation	Rubber Tired Dozers	Diesel	Average	3.00	8.00	367	0.40
Site Preparation	Tractors/Loaders/Back hoes	Diesel	Average	4.00	8.00	84.0	0.37
Grading	Excavators	Diesel	Average	2.00	8.00	36.0	0.38
Grading	Graders	Diesel	Average	1.00	8.00	148	0.41
Grading	Rubber Tired Dozers	Diesel	Average	1.00	8.00	367	0.40
Grading	Scrapers	Diesel	Average	2.00	8.00	423	0.48
Grading	Tractors/Loaders/Back hoes	Diesel	Average	2.00	8.00	84.0	0.37
Building Construction	Cranes	Diesel	Average	1.00	7.00	367	0.29
Building Construction	Forklifts	Diesel	Average	3.00	8.00	82.0	0.20
Building Construction	Generator Sets	Diesel	Average	1.00	8.00	14.0	0.74
Building Construction	Tractors/Loaders/Back hoes	Diesel	Average	3.00	7.00	84.0	0.37
Building Construction	Welders	Diesel	Average	1.00	8.00	46.0	0.45
Paving	Pavers	Diesel	Average	2.00	8.00	81.0	0.42
Paving	Paving Equipment	Diesel	Average	2.00	8.00	89.0	0.36
Paving	Rollers	Diesel	Average	2.00	8.00	36.0	0.38
Architectural Coating	Air Compressors	Diesel	Average	1.00	6.00	37.0	0.48

5.3. Construction Vehicles

5.3.1. Unmitigated

Phase Name	Trip Type	One-Way Trips per Day	Miles per Trip	Vehicle Mix
Site Preparation	—	—	—	—
Site Preparation	Worker	17.5	18.5	LDA,LDT1,LDT2
Site Preparation	Vendor	—	10.2	HHDT,MHDT
Site Preparation	Hauling	0.00	20.0	HHDT
Site Preparation	Onsite truck	—	—	HHDT
Grading	—	—	—	—
Grading	Worker	20.0	18.5	LDA,LDT1,LDT2
Grading	Vendor	—	10.2	HHDT,MHDT
Grading	Hauling	41.7	20.0	HHDT
Grading	Onsite truck	—	—	HHDT
Building Construction	—	—	—	—
Building Construction	Worker	99.4	18.5	LDA,LDT1,LDT2
Building Construction	Vendor	14.8	10.2	HHDT,MHDT
Building Construction	Hauling	0.00	20.0	HHDT
Building Construction	Onsite truck	—	—	HHDT
Paving	—	—	—	—
Paving	Worker	15.0	18.5	LDA,LDT1,LDT2
Paving	Vendor	—	10.2	HHDT,MHDT
Paving	Hauling	0.00	20.0	HHDT
Paving	Onsite truck	—	—	HHDT
Architectural Coating	—	—	—	—
Architectural Coating	Worker	19.9	18.5	LDA,LDT1,LDT2
Architectural Coating	Vendor	—	10.2	HHDT,MHDT
Architectural Coating	Hauling	0.00	20.0	HHDT
Architectural Coating	Onsite truck	—	—	HHDT

5.4. Vehicles

5.4.1. Construction Vehicle Control Strategies

Non-applicable. No control strategies activated by user.

5.5. Architectural Coatings

Phase Name	Residential Interior Area Coated (sq ft)	Residential Exterior Area Coated (sq ft)	Non-Residential Interior Area Coated (sq ft)	Non-Residential Exterior Area Coated (sq ft)	Parking Area Coated (sq ft)
Architectural Coating	83,217	27,739	0.00	0.00	13,068

5.6. Dust Mitigation

5.6.1. Construction Earthmoving Activities

Phase Name	Material Imported (cy)	Material Exported (cy)	Acres Graded (acres)	Material Demolished (sq. ft.)	Acres Paved (acres)
Site Preparation	—	—	15.0	0.00	—
Grading	—	10,000	90.0	0.00	—
Paving	0.00	0.00	0.00	0.00	5.00

5.6.2. Construction Earthmoving Control Strategies

Control Strategies Applied	Frequency (per day)	PM10 Reduction	PM2.5 Reduction
Water Exposed Area	2	61%	61%

5.7. Construction Paving

Land Use	Area Paved (acres)	% Asphalt
Congregate Care (Assisted Living)	—	0%
Parking Lot	5.00	100%

5.8. Construction Electricity Consumption and Emissions Factors

kWh per Year and Emission Factor (lb/MWh)

Year	kWh per Year	CO2	CH4	N2O
2025	0.00	532	0.03	< 0.005
2026	0.00	532	0.03	< 0.005
2027	0.00	532	0.03	< 0.005

5.9. Operational Mobile Sources

5.9.1. Unmitigated

Land Use Type	Trips/Weekday	Trips/Saturday	Trips/Sunday	Trips/Year	VMT/Weekday	VMT/Saturday	VMT/Sunday	VMT/Year
Total all Land Uses	359	359	359	131,035	2,247	2,247	2,247	820,289

5.10. Operational Area Sources

5.10.1. Hearths

5.10.1.1. Unmitigated

5.10.2. Architectural Coatings

Residential Interior Area Coated (sq ft)	Residential Exterior Area Coated (sq ft)	Non-Residential Interior Area Coated (sq ft)	Non-Residential Exterior Area Coated (sq ft)	Parking Area Coated (sq ft)
83217.375	27,739	0.00	0.00	13,068

5.10.3. Landscape Equipment

Season	Unit	Value
Snow Days	day/yr	0.00
Summer Days	day/yr	180

5.11. Operational Energy Consumption

5.11.1. Unmitigated

Electricity (kWh/yr) and CO2 and CH4 and N2O and Natural Gas (kBTU/yr)

Land Use	Electricity (kWh/yr)	CO2	CH4	N2O	Natural Gas (kBTU/yr)
Congregate Care (Assisted Living)	595,630	532	0.0330	0.0040	1,523,131
Parking Lot	190,793	532	0.0330	0.0040	0.00

5.12. Operational Water and Wastewater Consumption

5.12.1. Unmitigated

Land Use	Indoor Water (gal/year)	Outdoor Water (gal/year)
Congregate Care (Assisted Living)	5,752,002	0.00
Parking Lot	0.00	442,771

5.13. Operational Waste Generation

5.13.1. Unmitigated

Land Use	Waste (ton/year)	Cogeneration (kWh/year)
Congregate Care (Assisted Living)	417	—
Parking Lot	0.00	—

5.14. Operational Refrigeration and Air Conditioning Equipment

5.14.1. Unmitigated

Land Use Type	Equipment Type	Refrigerant	GWP	Quantity (kg)	Operations Leak Rate	Service Leak Rate	Times Serviced
---------------	----------------	-------------	-----	---------------	----------------------	-------------------	----------------

Congregate Care (Assisted Living)	Average room A/C & Other residential A/C and heat pumps	R-410A	2,088	< 0.005	2.50	2.50	10.0
Congregate Care (Assisted Living)	Household refrigerators and/or freezers	R-134a	1,430	0.22	0.60	0.00	1.00

5.15. Operational Off-Road Equipment

5.15.1. Unmitigated

Equipment Type	Fuel Type	Engine Tier	Number per Day	Hours Per Day	Horsepower	Load Factor
----------------	-----------	-------------	----------------	---------------	------------	-------------

5.16. Stationary Sources

5.16.1. Emergency Generators and Fire Pumps

Equipment Type	Fuel Type	Number per Day	Hours per Day	Hours per Year	Horsepower	Load Factor
----------------	-----------	----------------	---------------	----------------	------------	-------------

5.16.2. Process Boilers

Equipment Type	Fuel Type	Number	Boiler Rating (MMBtu/hr)	Daily Heat Input (MMBtu/day)	Annual Heat Input (MMBtu/yr)
----------------	-----------	--------	--------------------------	------------------------------	------------------------------

5.17. User Defined

Equipment Type	Fuel Type
----------------	-----------

5.18. Vegetation

5.18.1. Land Use Change

5.18.1.1. Unmitigated

Vegetation Land Use Type	Vegetation Soil Type	Initial Acres	Final Acres
--------------------------	----------------------	---------------	-------------

5.18.1. Biomass Cover Type

5.18.1.1. Unmitigated

Biomass Cover Type	Initial Acres	Final Acres
--------------------	---------------	-------------

5.18.2. Sequestration

5.18.2.1. Unmitigated

Tree Type	Number	Electricity Saved (kWh/year)	Natural Gas Saved (btu/year)
-----------	--------	------------------------------	------------------------------

6. Climate Risk Detailed Report

6.1. Climate Risk Summary

Cal-Adapt midcentury 2040–2059 average projections for four hazards are reported below for your project location. These are under Representation Concentration Pathway (RCP) 8.5 which assumes GHG emissions will continue to rise strongly through 2050 and then plateau around 2100.

Climate Hazard	Result for Project Location	Unit
Temperature and Extreme Heat	33.8	annual days of extreme heat
Extreme Precipitation	1.00	annual days with precipitation above 20 mm
Sea Level Rise	—	meters of inundation depth
Wildfire	0.00	annual hectares burned

Temperature and Extreme Heat data are for grid cell in which your project are located. The projection is based on the 98th historical percentile of daily maximum/minimum temperatures from observed historical data (32 climate model ensemble from Cal-Adapt, 2040–2059 average under RCP 8.5). Each grid cell is 6 kilometers (km) by 6 km, or 3.7 miles (mi) by 3.7 mi.

Extreme Precipitation data are for the grid cell in which your project are located. The threshold of 20 mm is equivalent to about $\frac{3}{4}$ an inch of rain, which would be light to moderate rainfall if received over a full day or heavy rain if received over a period of 2 to 4 hours. Each grid cell is 6 kilometers (km) by 6 km, or 3.7 miles (mi) by 3.7 mi.

Sea Level Rise data are for the grid cell in which your project are located. The projections are from Radke et al. (2017), as reported in Cal-Adapt (Radke et al., 2017, CEC-500-2017-008), and consider inundation location and depth for the San Francisco Bay, the Sacramento-San Joaquin River Delta and California coast resulting different increments of sea level rise coupled with extreme storm events. Users may select from four scenarios to view the range in potential inundation depth for the grid cell. The four scenarios are: No rise, 0.5 meter, 1.0 meter, 1.41 meters

Wildfire data are for the grid cell in which your project are located. The projections are from UC Davis, as reported in Cal-Adapt (2040–2059 average under RCP 8.5), and consider historical data of climate, vegetation, population density, and large (> 400 ha) fire history. Users may select from four model simulations to view the range in potential wildfire probabilities for the grid cell. The four simulations make different assumptions about expected rainfall and temperature are: Warmer/drier (HadGEM2-ES), Cooler/wetter (CNRM-CM5), Average conditions (CanESM2), Range of different rainfall and temperature possibilities (MIROC5). Each grid cell is 6 kilometers (km) by 6 km, or 3.7 miles (mi) by 3.7 mi.

6.2. Initial Climate Risk Scores

Climate Hazard	Exposure Score	Sensitivity Score	Adaptive Capacity Score	Vulnerability Score
Temperature and Extreme Heat	4	0	0	N/A
Extreme Precipitation	N/A	N/A	N/A	N/A
Sea Level Rise	N/A	N/A	N/A	N/A
Wildfire	N/A	N/A	N/A	N/A
Flooding	N/A	N/A	N/A	N/A
Drought	0	0	0	N/A
Snowpack Reduction	N/A	N/A	N/A	N/A
Air Quality Degradation	N/A	N/A	N/A	N/A

The sensitivity score reflects the extent to which a project would be adversely affected by exposure to a climate hazard. Exposure is rated on a scale of 1 to 5, with a score of 5 representing the greatest exposure.

The adaptive capacity of a project refers to its ability to manage and reduce vulnerabilities from projected climate hazards. Adaptive capacity is rated on a scale of 1 to 5, with a score of 5 representing the greatest ability to adapt.

The overall vulnerability scores are calculated based on the potential impacts and adaptive capacity assessments for each hazard. Scores do not include implementation of climate risk reduction measures.

6.3. Adjusted Climate Risk Scores

Climate Hazard	Exposure Score	Sensitivity Score	Adaptive Capacity Score	Vulnerability Score
Temperature and Extreme Heat	4	1	1	4
Extreme Precipitation	N/A	N/A	N/A	N/A
Sea Level Rise	N/A	N/A	N/A	N/A
Wildfire	N/A	N/A	N/A	N/A
Flooding	N/A	N/A	N/A	N/A
Drought	1	1	1	2
Snowpack Reduction	N/A	N/A	N/A	N/A
Air Quality Degradation	N/A	N/A	N/A	N/A

The sensitivity score reflects the extent to which a project would be adversely affected by exposure to a climate hazard. Exposure is rated on a scale of 1 to 5, with a score of 5 representing the greatest exposure.

The adaptive capacity of a project refers to its ability to manage and reduce vulnerabilities from projected climate hazards. Adaptive capacity is rated on a scale of 1 to 5, with a score of 5 representing the greatest ability to adapt.

The overall vulnerability scores are calculated based on the potential impacts and adaptive capacity assessments for each hazard. Scores include implementation of climate risk reduction measures.

6.4. Climate Risk Reduction Measures

7. Health and Equity Details

7.1. CalEnviroScreen 4.0 Scores

The maximum CalEnviroScreen score is 100. A high score (i.e., greater than 50) reflects a higher pollution burden compared to other census tracts in the state.

Indicator	Result for Project Census Tract
Exposure Indicators	—
AQ-Ozone	91.1
AQ-PM	19.7
AQ-DPM	20.8
Drinking Water	30.2
Lead Risk Housing	12.8
Pesticides	0.00
Toxic Releases	21.4
Traffic	25.9
Effect Indicators	—
CleanUp Sites	0.00
Groundwater	0.00
Haz Waste Facilities/Generators	50.1
Impaired Water Bodies	0.00
Solid Waste	59.2
Sensitive Population	—
Asthma	88.3
Cardio-vascular	99.8
Low Birth Weights	76.0

Socioeconomic Factor Indicators	—
Education	64.3
Housing	60.9
Linguistic	—
Poverty	37.4
Unemployment	25.2

7.2. Healthy Places Index Scores

The maximum Health Places Index score is 100. A high score (i.e., greater than 50) reflects healthier community conditions compared to other census tracts in the state.

Indicator	Result for Project Census Tract
Economic	—
Above Poverty	52.23918902
Employed	23.22597203
Median HI	59.20698062
Education	—
Bachelor's or higher	27.48620557
High school enrollment	100
Preschool enrollment	7.35275247
Transportation	—
Auto Access	77.83908636
Active commuting	1.039394328
Social	—
2-parent households	13.02450917
Voting	37.79032465
Neighborhood	—
Alcohol availability	92.09547029
Park access	20.46708585
Retail density	12.26741948

Supermarket access	16.14269216
Tree canopy	1.244706788
Housing	—
Homeownership	79.23777749
Housing habitability	49.21083023
Low-inc homeowner severe housing cost burden	44.83510843
Low-inc renter severe housing cost burden	19.08122674
Uncrowded housing	27.62735789
Health Outcomes	—
Insured adults	58.96317208
Arthritis	59.3
Asthma ER Admissions	12.1
High Blood Pressure	65.9
Cancer (excluding skin)	71.8
Asthma	25.7
Coronary Heart Disease	72.1
Chronic Obstructive Pulmonary Disease	45.1
Diagnosed Diabetes	50.0
Life Expectancy at Birth	18.5
Cognitively Disabled	85.7
Physically Disabled	74.5
Heart Attack ER Admissions	0.6
Mental Health Not Good	31.8
Chronic Kidney Disease	64.9
Obesity	27.3
Pedestrian Injuries	39.4
Physical Health Not Good	40.7
Stroke	58.2

Health Risk Behaviors	—
Binge Drinking	30.9
Current Smoker	30.4
No Leisure Time for Physical Activity	45.0
Climate Change Exposures	—
Wildfire Risk	0.0
SLR Inundation Area	0.0
Children	9.5
Elderly	81.9
English Speaking	55.8
Foreign-born	27.1
Outdoor Workers	34.3
Climate Change Adaptive Capacity	—
Impervious Surface Cover	74.6
Traffic Density	43.1
Traffic Access	23.0
Other Indices	—
Hardship	67.9
Other Decision Support	—
2016 Voting	42.2

7.3. Overall Health & Equity Scores

Metric	Result for Project Census Tract
CalEnviroScreen 4.0 Score for Project Location (a)	42.0
Healthy Places Index Score for Project Location (b)	35.0
Project Located in a Designated Disadvantaged Community (Senate Bill 535)	No
Project Located in a Low-Income Community (Assembly Bill 1550)	No
Project Located in a Community Air Protection Program Community (Assembly Bill 617)	No

a: The maximum CalEnviroScreen score is 100. A high score (i.e., greater than 50) reflects a higher pollution burden compared to other census tracts in the state.

b: The maximum Health Places Index score is 100. A high score (i.e., greater than 50) reflects healthier community conditions compared to other census tracts in the state.

7.4. Health & Equity Measures

No Health & Equity Measures selected.

7.5. Evaluation Scorecard

Health & Equity Evaluation Scorecard not completed.

7.6. Health & Equity Custom Measures

No Health & Equity Custom Measures created.

8. User Changes to Default Data

Screen	Justification
Land Use	Per project description
Construction: Construction Phases	Adjusted for construction timeline from 9/26/2025 to 4/30/2027
Operations: Hearths	No hearths

Appendix B:

EMFAC2021 Output

Source: EMFAC2021 (v1.0.2) Emissions Inventory

Region Type: Sub-Area

Region: San Bernardino (MD)

Calendar Year: 2027

Season: Annual

Vehicle Classification: EMFAC2007 Categories

Units: miles/day for CVMT and EVMT, trips/day for Trips, kWh/day for Energy Consumption, tons/day for Emissions, 1000 gallons/day for Fuel Consumption

Region	Calendar Year	Vehicle Category	Model Year	Speed	Fuel	Total VMT	Fuel Consumption	Total Fuel Consumption	Total VMT	MPG	Vehicle Category
San Bernardino (MD)	2027	HHDT	Aggregate	Aggregate	Gasoline	174.2440566	0.041192773	432.0026885	2820957.842	6.529954366	HHDT
San Bernardino (MD)	2027	HHDT	Aggregate	Aggregate	Diesel	2820783.598	431.9614958				
San Bernardino (MD)	2027	LDA	Aggregate	Aggregate	Gasoline	12731878.05	411.1416484	411.7454051	12757597.07	30.98418808	LDA
San Bernardino (MD)	2027	LDA	Aggregate	Aggregate	Diesel	25719.02477	0.603756671				
San Bernardino (MD)	2027	LDT1	Aggregate	Aggregate	Gasoline	980711.821	38.53767219	38.54044541	980779.7995	25.44806603	LDT1
San Bernardino (MD)	2027	LDT1	Aggregate	Aggregate	Diesel	67.97847461	0.002773222				
San Bernardino (MD)	2027	LDT2	Aggregate	Aggregate	Gasoline	6012722.206	235.2207429	235.8525125	6034160.355	25.58446502	LDT2
San Bernardino (MD)	2027	LDT2	Aggregate	Aggregate	Diesel	21438.14839	0.631769614				
San Bernardino (MD)	2027	LHDT1	Aggregate	Aggregate	Gasoline	464329.1064	32.94415895	51.46790578	846911.6911	16.45514186	LHDT1
San Bernardino (MD)	2027	LHDT1	Aggregate	Aggregate	Diesel	382582.5848	18.52374683				
San Bernardino (MD)	2027	LHDT2	Aggregate	Aggregate	Gasoline	60008.19906	4.810685273	14.80673288	232732.9478	15.71804865	LHDT2
San Bernardino (MD)	2027	LHDT2	Aggregate	Aggregate	Diesel	172724.7487	9.996047611				
San Bernardino (MD)	2027	MDV	Aggregate	Aggregate	Gasoline	4066676.874	199.2739452	201.9320699	4130653.879	20.45566056	MDV
San Bernardino (MD)	2027	MDV	Aggregate	Aggregate	Diesel	63977.00557	2.658124755				
San Bernardino (MD)	2027	MHDT	Aggregate	Aggregate	Gasoline	63572.61874	11.94882571	29.72544264	228439.9362	7.684996954	MHDT
San Bernardino (MD)	2027	MHDT	Aggregate	Aggregate	Diesel	164867.3175	17.77661694				