MOJAVE RIVER WATERSHED Water Quality Management Plan

For:

FIRE STATION 305 PREFABRICATED METAL STORAGE BUILDING

APN 3039-351-09, PM. NO. 18615

Prepared for:

San Bernardino County Project & Facilities Man. granei t Department

8331 Caliente P

Hesperia, CA . 22 +4

(760) 948-7, 58

repared by:

Engineering Resources Of Southern California Inc.

1361 W. Redlands Blvd.

Redlands, CA 92733

(909) 890-1255

Submittal Date: February 2024

Revision No. and Date: Insert No and Current Revision Date

Revision No. and Date: Insert No and Current Revision Date

Revision No. and Date: Insert No and Current Revision Date

Revision No. and Date: Insert No and Current Revision Date

Revision No. and Date: <u>Insert No and Current Revision Date</u>

Final Approval Date:_____

Project Owner's Certification

This Mojave River Watershed Water Quality Management Plan (WQMP) has been prepared for San Bernardino County by Engineering Resources Of Southern california Inc. The WQMP is intended to comply with the requirements of the San Bernardino County and the Phase II Small MS4 General Permit for the Mojave River Watershed. The undersigned, while it owns the subject property, is responsible for the implementation of the provisions of this plan and will ensure that this plan is amended as appropriate to reflect up-to-date conditions on the site consistent with the Phase II Small MS4 Permit and the intent of San Bernardino County (unincorporated areas of Phelan, Oak Hills, Spring Valley Lake and Victorville) and the incorporated cities of Hesperia and Victorville and the Town of Apple Valley. Once the undersigned transfers its interest in the property, its successors in interest and the city/county/town shall be notified of the transfer. The new owner will be informed of its responsibility under this WQMP. A copy of the approved WQMP shall be available on the subject site in perpetuity.

"I certify under a penalty of law that the provisions (implementation, peration, maintenance, and funding) of the WQMP have been accepted and that the plan win be cran ferred to future successors."

	THE RESIDENCE OF THE PROPERTY						
	Project . 'ata						
Permit/Application Number(s): Aradh a Permit Number(s):							
Tract/Parcel Map Number(s): 18615 b. 'Iding Permit Number(s):							
CUP, SUP, and/	CUP, SUP, and/or APN (Specify Lot Numbers in Portions of Tract): 303935109						
	Owner's Signature						
Owner Name	Bertral Wa hington						
Title	Deputy Chief of Administration						
Company	San Bernardino County Fire Protection District						
Address	157 W. 5th Street, 2nd Floor San Bernardino, CA 92415						
Email	bwashington@sbcfire.org						
Telephone #	(909) 387-5974						
Signature	12112	Date 10 18 2023					

Preparer's Certification

Project Data					
Permit/Application Number(s):		Grading Permit Number(s):			
Tract/Parcel Map Number(s):	18615	Building Permit Number(s):			
CUP, SUP, and/or APN (Specify Lot Numbers if Portions of Tract): 3039-351-09					

"The selection, sizing and design of stormwater treatment and other stormwater, quality and quantity control measures in this plan were prepared under my oversight and proctupe requirements of the California State Water Resources Control Board Order No. 2013-0c°1-DV Q.

Engineer: Mat	tt Brudin	PE Stamp Below
Title	Principal Engineer	DROFESS/O4
Company	Engineering Resources	BRUD CO
Address	1861 W. Redlands Blvd, P. dlands Ca 923/3	18/8/ ZZ
Email	MATT@ERSCINC	(2) (1836) 9
Telephone #	909-890-1255	*\
Signature	W the	OF CALIFORNIA
Date	10/18/2023	ST CALL

Table of Contents

Section I	Introduction	
Section 1	Discretionary Permits	1-1
Section 2	Project Description	2-1
	2.1 Project Information	2-1
	2.2 Property Ownership / Management	2-2
	2.3 Potential Stormwater Pollutants	2-3
	2.4 Water Quality Credits	2-4
Section 3	Site and Watershed Description	3-1
Section 4	Best Management Practices	4-1
	4.1 Source Control and Site Design BMPs	4-1
	4.1.1 Source Control BMPs	4-1
	4.1.2 Site Design RMPs	4-6
	4.2 Treatment BMPs 4.3 Project Conformance Analysis	4-7
	4.3 Project Conformance Analysis	4-12
	4.3.1 Site Design BMP	4-14
	4.3.2 Intiltration BiviP	4-16
	4.3.4 Biotreatment BMP	4-19
	4.3.5 Conformance Summary	4-23
	4.3.6 Hydromodification Control BMP	4-24
	4.4 Alternative Compliance Plan (if ap licable	4-25
Section 5	Inspection & Maintenance Res; onsilility rost Construction BMPs	5-1
Section 6	Site Plan and Drainage Plan	6-1
	6.1. Site Plan and Drain Plan Plan	6-1
	6.2 Electronic Data Submitta	6-1
Forms		
Form 1-1 l	Project Informatio.	1-1
	Description of Proposed Project	2-1
	L Property Ownership/Management	2-2
Form 2.3-	L Pollutants of Concern	2-3
Form 2.4-	L Water Quality Credits	2-4
Form 3-1	Site Location and Hydrologic Features	3-1
Form 3-2 I	Hydrologic Characteristics	3-2
Form 3-3 \	Natershed Description	3-3
Form 4.1-	I Non-Structural Source Control BMP	4-2
Form 4.1-2	2 Structural Source Control BMP	4-4
Form 4.1-3	Site Design Practices Checklist	4-6
Form 4.2-	LID BMP Performance Criteria for Design Capture Volume	4-7
Form 4.2-2	2 Summary of Hydromodification Assessment	4-8
Form 4.2-3	B Hydromodification Assessment for Runoff Volume	4-9
Form 4.2-	4 Hydromodification Assessment for Time of Concentration	4-10

Form 4.2-5 Hydromodification Assessment for Peak Runoff	4-11
Form 4.3-1 Infiltration BMP Feasibility	4-13
Form 4.3-2 Site Design BMP	4-14
Form 4.3-3 Infiltration LID BMP	4-17
Form 4.3-4 Selection and Evaluation of Biotreatment BMP	4-19
Form 4.3-5 Volume Based Biotreatment – Bioretention and Planter Boxes w/Underdrains	4-20
Form 4.3-6 Volume Based Biotreatment- Constructed Wetlands and Extended Detention	4-21
Form 4.3-7 Flow Based Biotreatment	4-22
Form 4.3-8 Conformance Summary and Alternative Compliance Volume Estimate	4-23
Form 4.3-9 Hydromodification Control BMP	4-24
Form 5-1 BMP Inspection and Maintenance	5-1

Appendix A: WQMP Plan and Architecture

Appendix B: National Resources Conservation Services (NRCS) report

Appendix C: Infiltration Report

Appendix D: NOAA14

Appendix E: Figure C-3, C-6 and D-1


Appendix F: FEMA Panel

Contents

Section I – Introduction

This WQMP template has been prepared specifically for the Phase II Small MS4 General Permit in the Mojave River Watershed. This location is within the jurisdiction of the Lahontan Regional Water Quality Control Board (LRWQCB). This document should not be confused with the WQMP template for the Santa Ana Phase I area of San Bernardino County.

WQMP preparers must refer to the MS4 Permit for the Mojave Watershed WQMP template and Technical Guidance (TGD) document found at: http://cms.sbcounty.gov/dpw/Land/NPDES.aspx to find pertinent arid region and Mojave River Watershed specific references and requirements.



Section 1 Discretionary Permit(s)

Form 1-1 Project Information						
Project Nai	me	Fire Station 305-Pr	refabricated	Metal Storage Building		
Project Ow	ner Contact Name:					
Mailing Address:			E-mail Address:		Telephone:	
Permit/App	plication Number(s):			Tract/Parcel Map Number(s):	18615	
Additional	Information/					
Comments	:			0)	,	
Description	Fire Station 305 will undergo construction to an act a brand-new prefabricated metal buil spanning approximately 4,000 square feet. Additionally, the construction of pavement of 10,482 square feet will be constructed to complement the building. This facility will see as a dedicated space to the refine trucks and store related equipment. The total disturbinarea is approximately 25,670 square feet.					f pavement area acility will serve
WQMP cor	mmary of Conceptual nditions (if pres out) and approved). A tach copy.					

Section 2 Project Description

2.1 Project Information

The WQMP shall provide the information listed below. The information provided for Conceptual/ Preliminary WQMP should give sufficient detail to identify the major proposed site design and LID BMPs and other anticipated water quality features that impact site planning. Final Project WQMP must specifically identify all BMP incorporated into the final site design and provide other detailed information as described herein.

The purpose of this information is to help determine the applicable development category, pollutants of concern, watershed description, and long term maintenance responsibilities for the project, and any applicable water quality credits. This information will be used in conjunction with the information in Section 3, Site Description, to establish the performance criteria and to select the TD BMP or other BMP for the project or other alternative programs that the project will participate in, which are described in Section 4.

2.1.1 Project Sizing Categorization

If the Project is greater than 5,000 square feet, and not on the excuder list as found on Section 1.4 of the TGD, the Project is a Regulated Development Project.

If the Project is creating and/or replacing greater than 2,750 square feet but less than 5,000 square feet of impervious surface area, then it is considered a lite De ign. Only project. This criterion is applicable to all development types including detached single far ily hor less that create and/or replace greater than 2,500 square feet of impervious area and are not part of a larger plan of development.

Form 2.1-1 Lescription of Proposed Project								
1 Regulated Developm	nent Proje	ct (atego	ry (elect all that apply):					
#1 New development involving the creation of 5, 70 addition or replacement of surface collectively over entire site #2 significant re- "42 significant re- "5 poment involving the addition or replacement of surface on an already developed site #3 Road Project – any road, sidewalk, or bicycle lane project that creates greater than 5,000 square feet of contiguous impervious surface #4 LUPs – linear underground/overhead projects that has a discrete location with 5,000 sq. ft. or more new constructed impervious surface				erground/overhead ects that has a rete location with 0 sq. ft. or more				
Site Design Only (Project Total Square Feet > 2,500 but < 5,000 sq.ft.) Will require source control Site Design Measures. Use the "PCMP" Template. Do not use this WQMP Template.								
Project Area (ft2):	oject Area (ft2): 25,670 3 Numbe		³ Number of Dwelling Units:		1	4 SIC C	4 SIC Code: 9224	
Is Project going to be phased? Yes No If yes, ensure that the WQMP evaluates each phase as a distinct DA, requiring LID BMPs to address runoff at time of completion.								

2.2 Property Ownership/Management

Describe the ownership/management of all portions of the project and site. State whether any infrastructure will transfer to public agencies (City, County, Caltrans, etc.) after project completion. State if a homeowners or property owners association will be formed and be responsible for the long-term maintenance of project stormwater facilities. Describe any lot-level stormwater features that will be the responsibility of individual property owners.



2.3 Potential Stormwater Pollutants

Best Management Practices (BMP) measures for pollutant generating activities and sources shall be designed consistent with recommendations from the CASQA Stormwater BMP Handbook for New Development and Redevelopment (or an equivalent manual). Pollutant generating activities must be considered when determining the overall pollutants of concern for the Project as presented in Form 2.3-1.

Determine and describe expected stormwater pollutants of concern based on land uses and site activities (refer to Table 3-2 in the TGD for WQMP).

Form 2.3-1 Pollutants of Concern						
Pollutant	Please check: E=Expected, N=Not Expected		Additional Cormac on and Comments			
Pathogens (Bacterial / Virus)	E 🔀	N 🗌	See table > 2 in the TG for WQM			
Nutrients - Phosphorous	E 🔀	Ν□	See Jable 3-2 in the TG for WQMP			
Nutrients - Nitrogen	E 🔀	N 🗌	See table 3-2 in the TG for WQM			
Noxious Aquatic Plants	E 🖂	ΝŪ	See table 3-2 in the TG for WQM			
Sediment	E 🖂	N	See table 3-2 in the TG for WQM			
Metals	-5	y 🗆	See table 3-2 in the TG for WQM			
Oil and Grease	M	N 🗌	See table 3-2 in the TG for WQM			
Trash/Debris	E 🖂	N 🗌	See table 3-2 in the TG for WQM			
Pesticides / Herbicides	E 🔀	Ν□	See table 3-2 in the TG for WQM			
Organic Compounds	E 🔀	N 🗌	See table 3-2 in the TG for WQM			
Other:	E 🗌	Ν□				
Other:	E 🗌	Ν□				
Other:	E	ΝΠ				

Section 3 Site and Watershed Description

Describe the project site conditions that will facilitate the selection of BMPs through an analysis of the physical conditions and limitations of the site and its receiving waters. Identify distinct drainage areas (DA) that collect flow from a portion of the site and describe how runoff from each DA (and sub-watershed Drainage Management Areas (DMAs)) is conveyed to the site outlet(s). Refer to Section 3.2 in the TGD for WQMP. The form below is provided as an example. Then complete Forms 3.2 and 3.3 for each DA on the project site. If the project has more than one drainage area for stormwater management, then complete additional versions of these forms for each DA / outlet. A map presenting the DMAs must be included as an appendix to the WQMP document.

Form 3-1 Site Location and Hydrolog c Fe≀ tures						
Site coordinates take GPS measurement at approximate center of site	e Latit	cude 34.4016	Longitud11	73	Thomas Bros Map page	
1 San Bernardino County c	limatic region:	□ Desert	0			
	ing DMAs and hy	drologic feature con ectir	ng DN \s to the site outlet(s). An exam	yes, then use this form to show a ple is provided below that can be	
Conveyance	Briefly describ	e on-site drainage feat	ures to convey runoff t	hat is not r	etained within a DMA	
DA1 DMA C flows to DA1 DMA A			oswale with 4' bottom wid g catch basin on SE corner		slopes and bed slope of 0.01. Conveys	
DA1 DMA A to Outlet 1						
DA1 DMA B to Outlet 1						
DA2 to Outlet 2						

Form 3-2 Existing Hydro	ologic Chara	acteristics fo	or Drainage	Area 1
For Drainage Area 1's sub-watershed DMA, provide the following characteristics	DMA A	DMA B	DMA C	DMA D
¹ DMA drainage area (ft²)	25,670			
2 Existing site impervious area (ft²)	0			
Antecedent moisture condition For desert areas, use http://www.sbcounty.gov/dpw/floodcontrol/pdf/2 0100412 map.pdf	II	\$		
4 Hydrologic soil group Refer to County Hydrology Manual Addendum for Arid Regions – http://www.sbcounty.gov/dpw/floodcontrol/pdf/2 0100412_addendum.pdf	А	7		
5 Longest flowpath length (ft)	1 7			
6 Longest flowpath slope (ft/ft)	0.01			
7 Current land cover type(s) <i>Select from Fig Coof Hydrology Manual</i>	32			
Pre-developed pervious are a condition: Based on the extent of wet season variated cover good >75%; Fair 50-75%; Poir 2000. ach photos of site to support ruling	75%			

Form 3-2 Existing Hydro (use only as need	_			
For Drainage Area 1's sub-watershed DMA, provide the following characteristics	DMA E	DMA F	DMA G	DMA H
$f{1}$ DMA drainage area (ft 2)				
2 Existing site impervious area (ft²)				
Antecedent moisture condition For desert areas, use http://www.sbcounty.gov/dpw/floodcontrol/pdf/2 0100412 map.pdf				
Hydrologic soil group County Hydrology Manual Addendum for Arid Regions – http://www.sbcounty.gov/dpw/floodcontrol/pdf/2 0100412_addendum.pdf				
5 Longest flowpath length (ft)				
6 Longest flowpath slope (ft/ft)				
7 Current land cover type(s) Select from Fig C-3 of Hydrology Manual				
8 Pre-developed pervious area condition: Based on the extent of wet season veletated color good >75%; Fair 50-75%; Poor <50%, ttach pho os of site to support rating				

Form 3-3 Watershed Description for Drainage Area					
Receiving waters					
Refer to SWRCB site:					
http://www.waterboards.ca.gov/water_issues/ programs/tmdl/integrated2010.shtml	Mojave River				
Applicable TMDLs					
http://www.waterboards.ca.gov/water_issues/progr ams/tmdl/integrated2010.shtml	5A				
303(d) listed impairments http://www.waterboards.ca.gov/water_issues/progr ams/tmdl/integrated2010.shtml	Fluoride, Sodium, Sufates, Magana, ese, vigen, dissolved, total disolved solids				
Environmentally Sensitive Areas (ESA) Refer to Watershed Mapping Tool – http://sbcounty.permitrack.com/WAP	None				
Hydromodification Assessment	Yes Complete Hydromodification Assessment. Include Forms 4.2-2 through Form 4.2-5 and Hydromodification BMP Form 4.3-9 in submittal No				

Section 4 Best Management Practices (BMP)

4.1 Source Control BMPs and Site Design BMP Measures

The information and data in this section are required for both Regulated Development and Site Design Only Projects. Source Control BMPs and Site Design BMP Measures are the basis of site-specific pollution management.

4.1.1 Source Control BMPs

Non-structural and structural source control BMP are required to be incorporated into all new development and significant redevelopment projects. Form 4.1-1 and 4.1-2 are used to describe specific source control BMPs used in the WQMP or to explain why a certain BMP is not applicable. Table 7-3 of the TGD for WQ 1P provides a list of applicable source control BMP for projects with specific types of potential pollutant sources or activities. The source control BMP in this table must be implemented for projects with these specific types of potential, of table activities.

The preparers of this WQMP have reviewed the source control BMP requirements for new development and significant redevelopment projects. The preparers have also reviewed the specific BL P required for project as specified in Forms 4.1-1 and 4.1-2. All applicable non-structural and structural source control BMP shall be implemented in the project.

The identified list of source control BMPs correspond to the CA. QA Stormwater BMP Handbook for New Development and Redevelopment.

	Form 4.1-1 Non-Structural Source Control BMPs								
		Check One		Describe BMP Implementation OR,					
Identifier	Name	Included	Not Applicable	if not applicable, state reason					
N1	Education of Property Owners, Tenants and Occupants on Stormwater BMPs	\boxtimes		The owner will implement sood is usekeeping practices. The owner will periodically provide environmental twarene is education materials, made available by the municipalities to all members, and proform education training before and after the rainy season.					
N2	Activity Restrictions		\boxtimes	No POA					
N3	Landscape Management BMPs			Implement CASQA BMP handbook SC-73 guidance. At a minimum, owner shall ensure it is a discover management BMPs are implemented(specify) including application of fertilizers/pesticides by licensed persons.					
N4	BMP Maintenance			Owner is responsible. See form 5-1.					
N5	Title 22 CCR Compliance (How development will comply)			No hazardous waste will be store on project site.					
N6	Local Water Quality Ordinances			Local Water Quality Ordinances will be addressed by implementation of this WQMP.					
N7	Spill Contingency Plan			Outdoor washing and cleaning runoff shall be capture by onsite storm drain and discharge into the proposed the onsite BMPs, (Locate spill cleanup materials, such a absorbents, where they will be readily accessible), vehicle maintenance and repair w be indoor whenever feasible, use drop cloths and drip pans. Parking areas post "No littering" signs and enforce anti littering laws. Minimum use absorbent materials on c spots prior to sweeping or washing and dispose of used absorbents appropriately.					
N8	Underground Storage Tank Compliance			No underground tank within the project site.					

	Form 4.1-1 Non-Structural Source Control BMPs						
N9	Hazardous Materials Disclosure Compliance			No Hazardous Materials will be management in the site			



	Form 4.1-1 Non-Structural Source Control BMPs								
		Che	ck One	Describe BMP Implementation OR,					
- Identifier	Name	Included	Not Applicable	if not applicable, state reason					
N10	Uniform Fire Code Implementation		\boxtimes	No fueling azarchus waste will be stored on the project site					
N11	Litter/Debris Control Program			Implement 'as' man agement and littler control daily and during landscape maintenance. Trash, vill 'e cleaned as need it. No heavy equipment will be allowed to use during BMPs cleaning.					
N12	Employee Training	\boxtimes		Owne mall train every new employee on WQMP requirements with latest updated education materials within 3 months of hiring and hold employee training on WQMP requirements on an annual basis.					
N13	Housekeeping of Loading Docks			No loading docks are proposed.					
N14	Catch Basin Inspection Program	×		The owners will have at least 80% of drainage inspected, cleaned and maintained on an annual basis with 100% of the facilities included in a two-year period.					
N15	Vacuum Sweeping of Private Streets and Parking Lots	M		Keep all parking areas clean and orderly. Remove debris, litter, and sediments in a timely fashion, Post "No Littering" signs and enforce antilitter laws. Clean out and cover litter receptacles frequently to prevent spillage, Provide an adequate number of litter receptacles.					
N16	Other Non-structural Measures for Public Agency Projects			No requirement by the local jurisdiction.					
N17	Comply with all other applicable NPDES permits			The site will comply with the NPDES permits.					

	Form 4.1-2 Structural Source Control BMPs								
		Che	ck One	Describe BMP Implementation OR,					
Identifier	Name	Included	Not Applicable	If not applicable, state reason					
S1	Provide storm drain system stencilling and signage (CASQA New Development BMP Handbook SD-13)			Implement CASQA BMP handbook SD-13 guidance. Legibility of markers and signs will be maintained year around.					
S2	Design and construct outdoor material storage areas to reduce pollution introduction (CASQA New Development BMP Handbook SD-34)		\boxtimes	No o tdoor naterial storage area proposed.					
S3	Design and construct trash and waste storage areas to reduce pollution introduction (CASQA New Development BMP Handbook SD-32)			No waste storage proposed.					
S4	Use efficient irrigation systems & landscape design, water conservation, smart controllers, and source control (Statewide Model Landscape Ordinance; CASQA New Development BMP Handbook SD-12)			No landscape areas proposed.					
S5	Finish grade of landscaped areas at a minimum of 1-2 inches below top of curb, sidewalk, or pavement		Ø	No landscape areas proposed					
S6	Protect slopes and channels and provide energy dissipation (CASQA New Development BMP Handbook SD-10)		\boxtimes	No steep slopes and channel proposed with the project site.					
S7	Covered dock areas (CASQA New Development BMP Handbook SD-31)	1 -1	\boxtimes	No proposed dock areas within the project site.					
S8	Covered maintenance bays with spill continment plans (CASQA New Development BMP Handbook SD-31)			No maintenance bays or Docks proposed.					
S9	Vehicle wash areas with spill containment plans (CASQA New Development BMP Handbook SD-33)			No vehicle wash areas proposed in the project site.					
S10	Covered outdoor processing areas (CASQA New Development BMP Handbook SD-36)			No processing areas proposed.					

	Form 4.1-2 Structural Source Control BMPs								
	Name	Check One		Describe BMP Implementation OR,					
Identifier		Included	Not Applicable	If not applicable, state reason					
S11	Equipment wash areas with spill containment plans (CASQA New Development BMP Handbook SD-33)		\boxtimes	N wash areas proposed.					
S12	Fueling areas (CASQA New Development BMP Handbook SD-30)			No fueling area proposed.					
S13	Hillside landscaping (CASQA New Development BMP Handbook SD-10)			No hillside landscape proposed.					
S14	Wash water control for food preparation areas			No food establishments proposed.					
S15	Community car wash racks (CASQA New Development BMP Handbook SD-33)		A	No carwash racks proposed.					

4.1.2 Site Design BMPs

As part of the planning phase of a project, the site design practices associated with new LID requirements in the Phase II Small MS4 Permit must be considered. Site design BMP measures can result in smaller Design Capture Volume (DCV) to be managed by both LID and hydromodification control BMPs by reducing runoff generation.

As is stated in the Permit, it is necessary to evaluate site conditions such as soil type(s), existing vegetation and flow paths will influence the overall site design.

Describe site design and drainage plan including:

- A narrative of site design practices utilized or rationale for not using practices
- A narrative of how site plan incorporates preventive site design practices
- Include an attached Site Plan layout which shows how preventative site up ign practices are included in WQMP

Refer to Section 5.2 of the TGD for WQMP for more details.

Form 4.1-3 Site Design Practice: Checklist
Site Design Practices If yes, explain how preventative site design practice is addressed in project cite p. in. If no, other LID BMPs must be selected to meet targets
Minimize impervious areas: Yes No Sexplanation: The runoff generated by the FS305 garage builds a and carking area will be directed through the surface and discharged into a bioretention system.
Maximize natural infiltration capacity; Including improvement and maintenance of soil: Yes No Explanation: Bioretention basin was propose 'to maximize the natural infiltration. The bioretention bmp aims to promote the infiltration of storm runoff from the site.
Preserve existing drainage patterns and time of concentration: Yes No No Explanation:
Disconnect impervious are a Incidency rerouting of rooftop drainage pipes to drain stormwater to storage or infiltration BMPs instead of to storm drain: Yes No
Explanation: Implemented area will be draining into a proposed Bioretention basin.
Use of Porous Pavement.: Yes No Explanation: No pourous paveent proposed.
Protect existing vegetation and sensitive areas: Yes 🔀 No 🗌
Explanation: No vegetation or sensitive areas exist within the project site.
Re-vegetate disturbed areas. Including planting and preservation of drought tolerant vegetation. : Yes 🗌 No 🔀 Explanation: No landscape has been proposed.

Minimize unnecessary compaction in stormwater retention/infiltration basin/trench areas: Yes No Explanation: No compaction is permitted within its limits of the bioretention basin construction. The limits of these bioretention basin are to be marked off during construction.
Utilize naturalized/rock-lined drainage swales in place of underground piping or imperviously lined swales: Yes No Explanation: The runoff generated by the site will flow freely over the proposed pavement and ultimately discharge into the proposed Bioretention basin.
Stake off areas that will be used for landscaping to minimize compaction during construction : Yes \(\sum \) No \(\sum \) Explanation: No landscape has been proposed.
Use of Rain Barrels and Cisterns, Including the use of on-site water collection systems.: Yes \(\subseteq\) No \(\subseteq\) Explanation: No rain barrels have been proposed.
Stream Setbacks. Includes a specified distance from an adjacent steam: : Yes \(\sum \) No \(\sum \) Explanation: No steam adjacent to the site.

It is noted that, in the Phase II Small MS4 Permit, site design elements or green roofs and vegetative swales are required. Due to the local climatology in the Mojave River Vatershed, proactive measures are taken to maximize the amount of drought tolerant vegetation. It is not practical in this region to have green roofs or vegetative swales. As part of site design the project property should utilize locally recommended vegetation types for landscaping. Typical landscaping recommendations are found in following local references:

San Bernardino County Special Districts:

Guide to High Desert Landscaping -

http://www.specialdistricts.org/Modules/s_owDocument.aspx?documentid=795

Recommended High-Desert Plan s -

http://www.specialdistricts.or./m.dule/showdocument.aspx?documentid=553

Mojave Water Agency:

Desert Ranch: http://www.mojavewater.org/files/desertranchgardenprototype.pdf

Summertree: http://www.mojavewater.org/files/Summertree-Native-Plant-Brochure.pdf

Thornless Garden: http://www.mojavewater.org/files/thornlessgardenprototype.pdf

Mediterranean Garden: http://www.mojavewater.org/files/mediterraneangardenprototype.pdf

Lush and Efficient Garden: http://www.mojavewater.org/files/lushandefficientgardenprototype.pdf

Alliance for Water Awareness and Conservation (AWAC) outdoor tips - http://hdawac.org/save-outdoors.html

4.2 Treatment BMPs

After implementation and design of both Source Control BMPs and Site Design BMP measures, any remaining runoff from impervious DMAs must be directed to one or more on-site, treatment BMPs (LID or biotreatment) designed to infiltrate, evaportranspire, and/or bioretain the amount of runoff specified in Permit Section E.12.e (ii)(c) Numeric Sizing Criteria for Storm Water Retention and Treatment.

4.2.1 Project Specific Hydrology Characterization

The purpose of this section of the Project WQMP is to establish targets for post-development hydrology based on performance criteria specified in Section E.12.e.ii.c and Section E.12.f of the Phase II Small MS4 Permit. These targets include runoff volume for water quality control (referred to as LID design capture volume), and runoff volume, time of concentration, and peak runoff for protection from hydromodification.

If the project has more than one outlet for stormwater runoff, then complete additional versions of these forms for each DA / outlet.

It is noted that in the Phase II Small MS4 Permit jurisdictions, the LD EMP Losign Capture Volume criteria is based on the 2-year rain event. The hydromodification performant crit rion is based on the 10-year rain event.

Methods applied in the following forms include:

• For LID BMP Design Capture Volume (DCV), San B rnardin County requires use of the P₆ method (Form 4.2-1) For pre- and post-development hydrologic calculation, San Bernardino County requires the use of the Rational Method (San Bernardino County regional Method (San Bernardino County regional Method D). Forms 4.2-2 through Form 4.2-5 calculate hydrologic variables including runofit colume, time of concentration, and peak runoff from the project site pre- and post-development using the Hydrology Manual Rational Method approach. For projects greater than 640 acres (1.0 mi²) the Rational Method and these forms should not be used. For such projects, the Unit Hydrograph Metho (San Ternardino County Hydrology Manual Section E) shall be applied for hydrologic calculations for two projects are referred.

Refer to Section 4 in the Top for waMP for detailed guidance and instructions.

Form 4.2-1 LID BMP Performance Criteria for Design Capture Volume (DA 1)								
¹ Project area DA 1 (ft ²): 25,670	DA 1 Imperviousness after applying preventative site design practices (Imp%): 56.42							
4 Determine 1-hour rainfa	ll depth for a 2-year return period P _{2yr-1hr} (in): 0.4	84 <u>http://hdsc.nws.noaa.gov/hdsc/</u>	pfds/sa/sca pfds.html					
	Precipitation (inches): 0.5988 function of site climatic region specified in Form 3-1 Item	n 1 (Desert = 1.2371)						
Drawdown Rate Use 48 hours as the default condition. Selection and use of the 24 hour drawdown time condition is subject to approval by the local jurisdiction. The necessary BMP footprint is a function of drawdown time. While shorter drawdown times reduce the performance criteria for LID BMP design capture volume, the depth of water that can be stoled is also reduced.								
DCV = 1/12 * [Item 1* Item 3	Compute design capture volume, DCV (ft ³): 962 $DCV = 1/12 * [Item 1* Item 3 * Item 5 * C2], where C2 is a function of drawdown rate (24-lh, = 1.5 \angle, - 2-hr = 1.963) Compute separate DCV for each outlet from the project site per schematic drawn in Form 3-1, em 2$							

Form 4.2-2 Summary of Hydromov ification Assessment (DA 1)								
Is the change in post- and pre- condition flows cap, ared on-site?: Yes No I If "Yes", then complete Hydromodification assessment of site hydrology for 10yr storm event using Forms 4.2-3 through 4.2-5 and insert results below (Fo. ns 4.2-3 through 4.2-5 may be replaced by computer software analysis based on the San Bernardino County Vidrology, Manual- Addendum 1) If "No," then proceed to Section 4.3 BM Selection and Sizing								
Condition	Runoff Volume (ft³)	Time of Concentration (min)	Peak Runoff (cfs)					
Pre-developed	1 412 Form 4.2-3 Item 12	2 6 Form 4.2-4 Item 13	³ 0.50 Form 4.2-5 Item 10					
Post-developed	4 2,265 Form 4.2-3 Item 13	⁵ 6.5 Form 4.2-4 Item 14	⁶ 0.91 Form 4.2-5 Item 14					
Difference 7 1,852 8 -0.50 9 0.41 Item 4 - Item 1 Item 5 Item 6 - Item 3								
Difference (as % of pre-developed)	10 450% Item 7 / Item 1	11 -8.33% Item 8 / Item 2	12 81% Item 9 / Item 3					

Form 4.2-3 Hy	/dromo	dificatio	n Asses	sment f	or Runo	ff Volur	ne (DA	1)	
Weighted Curve Number Determination for: <u>Pre</u> -developed DA	DMA A	DMA B	DMA C	DMA D	DMA E	DMA F	DMA G	DMA H	
1a Land Cover type	Commer.								
2a Hydrologic Soil Group (HSG)	Α								
3a DMA Area, ft ² sum of areas of DMA should equal area of DA	25,670								
4 a Curve Number (CN) use Items 1 and 2 to select the appropriate CN from Appendix C-2 of the TGD for WQMP	32								
Weighted Curve Number Determination for: <u>Post</u> -developed DA	DMA A	DMA B	DMA C	DMA D	DMA -	DMA F	DMA G	DMA H	
1b Land Cover type	Commer.								
2b Hydrologic Soil Group (HSG)	А								
3b DMA Area, ft ² sum of areas of DMA should equal area of DA	25,670		. (
4b Curve Number (CN) use Items 5 and 6 to select the appropriate CN from Appendix C-2 of the TGD for WQMP	85.36	/							
5 Pre-Developed area-weighted CN	l: 32	7 Pre-de elo		ge capacity, S ((in): 21.25	9 Initial at	ostraction, I _a (i Item 7	n): 4.25	
6 Post-Developed area-weighted C	N: 83 36	8 P st-develo	oped soil stora em 6) - 10	ge capacity, S	(in): 1.71	10 Initial a	abstraction, I _a	(in): 0.34	
	11 Precipitation for 10 yr, 24 hr ston. (in): 2.32 Go to: http://hdsc.nws.noaa.gov/hdsc/pja_/sa/sca_pfds.html								
12 Pre-developed Volume (ft ³): 412 V _{pre} =(1/12) * (Item sum of Item 3) * [(Item 11 – Item 9)^2 / ((Item 11 – Item 9 + Item 7)									
13 Post-developed Volume (ft³): 2,265 V _{pre} =(1 / 12) * (Item sum of Item 3) * [(Item 11 – Item 10)^2 / ((Item 11 – Item 10 + Item 8)									
14 Volume Reduction needed to meet hydromodification requirement, (ft^3): 1,739 Vhydro = (Item 13 * 0.95) – Item 12									